
Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



BARCO

Nazwa

Barco MDRC-2221 ATM 21-inch auxiliary display for Air Traffic Control

Cena

0,00 zł

Producent

Barco

OPIS PRODUKTU

Active screen diagonal

541 mm (21.3")

Screen technology

TFT Color LCD

Active screen area

432 mm x 324 mm (17" x 12.76")

Aspect Ratio

4:3

Native resolution

1600x1200

Pixel pitch

0.270 x 0.270 mm

Viewing angle

178°

Brightness

250 cd/m² (max typ 440 cd/m²)

Contrast ratio

1500:1

Video input signals

DP, DVI

Backlight Output Stabilization (BLOS)

yes

Backlight

LED - Backlight optical stabilization

Ambient Light Compensation (ALC)

yes, preset value in OSD

Touch screen

no

Power consumption

23 W nominal; less than 1.0 W in off/stand-by mode; DPMS support

Power requirements

100-250 V (nominal)

USB ports

1 upstream, 2 downstream

USB standard

2.0

Dimensions w/o stand (W x H x D)

376 x 484 x 75.93 mm (portrait)

484 x 376 x 75.93 mm (landscape)

Dimensions with stand (W x H x D)

376 x 591.7 x 201.33 mm (portrait)

484 x 537.7 x 201.33 mm (landscape)

Dimensions packaged (W x H x D)

584 x 667 x 272 mm

Net weight with stand

8.7 kg

Net weight w/o stand

5.25 kg

Net weight packaged with stand

12.4 kg

Height adjustment range

100 mm +/- 5.0 mm

Tilt

-5° / +20°

Swivel

-45° / +45°

Pivot

90°

Mounting standard

VESA (100 mm)

Certifications

CE (MDD 93/42/EEC class I product), CE - 2004/ 108/EC, IEC 60601-1:2005, ANSI/AAMI ES60601-1 (2005)/(R)2012 + C1:2009/(R)2012 + A2:2010/(R)2012), CAN/CSA-C22.2 No. 60601-1 (2008), DEMKO - EN 60601- 1:2006, EN 60601-1-2:2007, KC, VCCI, FCC class B, ICES-001 Level B, FDA Class I device, RoHS

Supplied accessories

User Guide

Cable routing strap

Video cables (1x DVI, 1x DP)

Main cables (UK, European (CEBEC/KEMA) or USA (UL/CSA))

Adaptor plug NEMA 5-15P)

USB 2.0 cable

This adaptor is a forming part of the device. (Manufacturer: BridgePower Corp.; Model: BPM060S24F09;

Input: 100-240 V AC, 50-60 Hz, 1.5 A; Output: +24 V DCV, 2.7 A)

Warranty

3 years