
Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



BARCO

Nazwa **OverView EVD-4621 46" near-seamless LCD video wall**

Cena **0,00 zł**

Producent **Barco**

OPIS PRODUKTU

LCD technology

S-PVA, normally black

Resolution

Full HD (1920 x 1080)

Backlight

Direct LED

Aspect Ratio

16:9

Pixel density

48 dpi

Refresh rate

60 Hz

Luminance

450 cd/m2 (typ.)

Contrast

3500:1 (typ.)

Viewing angle

H 178° | V 178°

White point

10,000 K

Color

10 bits - 1.07 B colors

Color calibration

Only manual (by eye) calibration

Precision

Internal 10 bit processing

Backlight lifetime

60,000 h (typ)

MTBF

100,000 h (half brightness)

Active screen diagonal

46" (1168 mm)

Dimensions

1024.0 x 578.6 x 98.2 mm | 40.3" x 22.8" x 3.9"

Active screen area

1018.1 mm x 572.7 mm | 40.1" x 22.6"

Bezel width

Right, bottom: 1.9 mm | 0.075"

Left, top: 3.8 mm | 0.13"

Total: 5.7 mm | 0.21"

Weight

26 kg | 57.3 lbs (net)

36 kg | 79.4 lbs (gross)

Cooling

Low noise fans

AC input voltage

100-240 VAC, 50-60 Hz

Power consumption

190 W (max) | 90 W (typ) | 20 W (sleep) | 2.5 W (stdby)

Heat dissipation

819 BTU/h (max)

DVI

Single link DVI-D in/out with HDCP

Resolution: (60Hz): 640x480, 800x600, 1024x768, 1280x1024, 1360x768, 1920x1200, 720p60, 1080p60;
1080p24, 1080p25, 1080p30, 1080p50

Remote Control

External dongle with approx. 1m 3.5mm Stereo Male to IR Receiver

Barco Wall Control Manager

BCMC Server connected via RS-232

Remote client application: on/off, wall set-up, source selection, status, brightness, contrast and color adjustments

Control signal

RS-232 DSUB9 in/out

Operating humidity

20-80%, non-condensing

Operational temperature

0 - 45°C | 32 - 109°F

Storage humidity

10-90%, non-condensing

Storage temperature

-20 - 60°C | -4 - 140°F

Safety

UL / c_UL / CB / TUV / KCC

EMI / EMC

EMC / IEC / FCC / CE / KCC