

## Inteligentna Elektronika

Ul. Raduńska 36A  
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



**BARCO**

Nazwa

**OverView OLS-721 Fully redundant 70" full HD 16:9 LED video wall with 3D**

Cena

**0,00 zł**

Producent

**Barco**

## OPIS PRODUKTU

Resolution

Full HD (1920 x 1080px)

Brightness

on-screen: 220/175 Cd/m<sup>2</sup> (typ.) in 2D/3D mode

On-screen contrast

560,000:1

Color

Up to 165% EBU (at maximum color mode)

Display technology

Rear projection DLP

White point

3,200/6,500/9,600/arbitrary

Screen

FXS, with H/V 34°/33° half gain angle

Screen gap

Hor: 1 mm | 0.04", Vert. 0.7 mm | 0.03" (@ 25°C)

Hor: < 0.4 mm | 0.015", Vert. < 0.3 mm | 0.012" (@ 30°C)

Screen gap with optional NoGap screen technology

Hor: 0.1 mm | 0.004"

Vert. 0.1 mm | 0.004"

All temperature/humidity conditions

Color stability

Self calibration with spectrometer based Sense6

Dimensions

• Diagonal: 70"

• Width: 1,550 mm | 61"

• Height: 872 mm | 34.3"

- Depth: 622 mm | 24.5"
- Weight: Projection Module: < 63 kg | 139 lbs
- Weight: Pedestal: < 39 kg | 86 lbs

Light source

6x redundancy for each of 3 LED's

Light source lifetime

> 60,000h (6500k)

> 80,000h (eco mode)

MTBF LED > 500,000 h

Power

350W (max)

230W (typ.)

170W (eco)

Signal

2x Dual link DVI in / 2x Dual link DVI out

Signal processing

Loop through

Free cropping, free scaling (optional)

Direct ethernet access

Built in web server

Graphical user interface

All settings and operational parameters

Accessibility & servicing

Back

Integration to third party equipment

WEB service API

Stereoscopic 3D

yes

Conditions for operation

10°C - 40°C, 50°F - 104°F, 80% humidity (non-condensing)

Heat dissipation

580 BTU/h (eco)

785 BTU/h (typ.)

1,194 BTU/h (max)

Warranty

2 years