

## Inteligentna Elektronika

Ul. Raduńska 36A  
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



**BARCO**

Nazwa **OverView OVL-715 Fully redundant 70" SXGA+ 4:3 LED video wall**

Cena **0,00 zł**

Producent **Barco**

## OPIS PRODUKTU

### Resolution

SXGA+ (1400x1050px)

### On-screen contrast

1,200,000 :1

### Color

Up to 165% EBU

### Display technology

rear-projection DLP

### White point

3,200K | 6,500K | 9,600K | arbitrary

### Brightness uniformity

Typ 95% ANSI 13

### Screen

BB, FXS, High Gain

### Screen gap

< 0.2 mm | 0.008" stitched

< 1.5 mm | 0.06" modular (@25°C)

< 0.4 mm | 0.015" modular (@30°C)

### Color stability

Self calibrating with spectrometer based Sense6

### Dimensions

• Diagonal: 70" nominal

• Width: 1,400 mm / 55.1"

• Height: 1,050 mm / 41.3"

• Depth: 899 mm / 35.4"

• Aspect ratio: 4:3

• Weight/module 101.5 kg / 224 lbs

Light source  
3x six fold redundant LED block  
Light source lifetime  
> 60,000 h, > 80,000 h (eco)  
Conditions for operation  
10°C-40°C, 50°F-104°F, 80% humidity (nc)  
AC input voltage  
90 – 240 V, 50-60Hz  
Power  
typical: 230W, maximum: 350W, eco mode: 170W  
Heat dissipation  
typical: 785, maximum: 1,194, eco mode: 580 BTU/h  
Direct ethernet access  
Build in web server  
Graphical user interface  
All settings and operational parameters  
Signal input/output  
2x Dual link DVI in, 2x Dual link DVI out  
Single link DVI in, with HDCP (optional)  
Pixel clock  
320 MHz  
Input frequency  
24 – 62 Hz  
Genlock  
49 – 61 Hz  
Signal processing  
Loop through up to 10 cubes / Free cropping, free scaling  
Integration to third party equipment  
Web based API  
Warranty  
2 years