

## Inteligentna Elektronika

Ul. Raduńska 36A  
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



Nazwa **Monitor Interaktywny BenQ RP7502**

Cena **0,00 zł**

Producent **BenQ**

## OPIS PRODUKTU

### Specyfikacje

Panel

Screen Size

75"

Resolution (pixels)

UHD 3840 x 2160 pixels

Backlight / Lightsource

DLED

Brightness (Typical) (nits)

450 nits

Contrast Ratio (Typical)

1,200:1

Viewing Angle (Horizontal / Vertical)

178°/178°

Light Life (Typical) (hours)

30,000 hours

Display Orientation

Landscape

Color Gamut (x% NTSC)

72%

Response Time (ms)

8ms

Touch

Touch Technology

IR

Number of Touch

USB B Touch Port x3

Glass

Tempered Glass

4mm Tempered Glass

Anti-Glare & Germ-Resistant Screen

Yes

Connectivity & Sensor

Connector

VGA x1, HDMI 2.0 x3, HDMI Out x1, 3.5mm Audio Line in/Mic in x1, 3.5mm Audio Line out x1, SPDIF Audio out x1, USB 2.0 x3, USB 3.0 x2, USB B Touch Port x3, Type C x1, RS232 x1, RJ45 x1, OPS Slot x1

Built-in Camera

No

Built-in Microphone

Array Microphone x8

Built-in speaker

Speakers 16W x2 & Subwoofer 15W x1

Sensor

NFC Sensor x1, Motion Sensor (PIR) x3, Air Quality Sensor x1, Light Sensor x1

Power

Voltage

AC 100-240V~ 50/60Hz

Typical (watt)

262.4 W

Mechanical

Weight (Without Packing / With Packing) (kg)

61 kg

Dimension (WxHxD) (mm)

1735.5 x 1085.8 x 130.7

Wall Mounting (VESA) (mm)(Screw type /Max. length)

4 holes (600 x 400mm) Screw M8 x 20mm

Handle

x2

Language

On-Screen Display Languages

English / French / German / Dutch / Polish / Russian / Czech / Danish / Swedish / Italian / Romanian / Finnish / Norwegian / Greek / Hungarian / Spanish / Portuguese / Traditional Chinese / Simplified / Chinese / Arabic / Japanese / Thai / Persian / Vietnamese / Korea / Turkey / indonesia (27L)

Package/Accessory

Cable

VGA x1, HDMI x1, USB for touch x1, TYPE-C x1

Quick Start Guide

x1

User's Manual (electronic file)

x1

Wall Mount (with shipment)

x1

Touch Pen

x2

Power Cord

By Region

Remote Controller (with 2.4G dongle & Battery)

