

---

## Inteligentna Elektronika

Ul. Raduńska 36A  
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl

---



Nazwa	<b>Projektor BenQ MH856UST+ (9H.JKT77.24E)</b>
Cena	<b>0,00 zł</b>
Producent	<b>BenQ</b>

---

## OPIS PRODUKTU

### Specyfikacja techniczna:

Interactive Projektor MH856UST+

Display

Projection System: DLP Single 0.65" Full HD

DMD Type: DC3 DMD Chip

Resolution: 1920 x 1080 pixels, 16:9

Brightness: 3,500 Lumens

Contrast Ratio: 10,000:1

Display Color: 1.07 Billion Colors

Aspect Ratio: Native 16:9 (5 aspect ratio selectable)

Light Source: Lamp (240W)

Light Source Life\*: Normal 5000 hrs;Economic 8000 hrs;SmartEco 10000 hrs;LampSave 12000 hrs

Optical

Throw Ratio: 0.33

Zoom Ratio: Fixed

Lens: F=2.5, f=5.1mm

Lens Shift: N/A

Lens Control: Manual Focus

Keystone Correction: 2D; Vertical  $\pm 15$  degrees, Horizontal  $\pm 15$  degrees

Projection Offset\*\*: 124 $\pm$ 5% (Full-Height)

Projection Size (diagonal): 89"~102" (with wall mount)

Audio

Built-in Speaker: 10W x2

#### Special Feature

Security Lock: Security Bar, Kensington anti-theft lock slot

Feature: 2D Keystone, Corner Fit, Digital zoom(2x), Digital Shrink(0.8x) and Shift, LAN Control, AMX/ PJ Link/Crestron/MDA,DMS Local Compatibility Optional Wireless Display, Optional Interactive module (PW30U/PT20) compatibility.

#### Connectivity

##### I/O Port

HDMI-1 x 1

HDMI-2 x 1

PC (D-sub 15pin) x 1

Monitor out (D-sub 15pin,Female) x 1

Composite Video in (RCA) x 1

Audio in(mini jack) x 1

Audio L/R in (RCA) x 1

Audio out (mini jack) x 1

LAN Port(RJ45 for Network ) x 1

RS232 In (D-sub 9pin, male) x 1

USB TypeA (5V,1.5A) x 1

USB Type B (For service) x 1

USB Type mini B (For PointWrite module) x 1

IR Receiver(Front) x 1

#### Compatibility

Resolution Support: VGA (640 x 480) to WUXGA (1920 x 1200)

Horizontal Frequency: 15K - 102kHz

Vertical Scan Rate: 23 - 120Hz

HDTV Compatibility: 480i, 480p, 576i, 576p, 720p, 1080i, 1080p

Video Compatibility: NTSC, PAL, SECAM

#### Power

Power Consumption (Max/Normal/Eco): Max 350W. Normal 320W. Eco 260W

Standby Power Consumption: Normal < 0.5Watts. Network < 2W.

Power Supply: 100 ~ 240V AC

#### Dimension and Weight

Product Dimensions (WxHxD): 287.5x 206.9 x 373.3 mm

Product Weight: 5 Kg+/- 100g

#### Operation Condition

Noise Level (Normal/Eco): 34/29 dBA

Operating Temperature: 0o ~ 40o C

#### Accessories

Accessories (Standard)

Power Cord (by region)

Remote Control (RCS011)

AAA Battery x2

VGA cable

Warranty Card (by region)

QSG (4J.JKS01.001)

Regulatory statement x1

Wall mount (WM04G4)

Accessories (Optional)

3D Glasses (5J.J9H25.002)

PointWrite Kit: PW30U (5A.JJR26.20E)

PointWrite Touch Module: PT20(5A.JJR26.30E)

Wireless Dongle: QCast Mirror (5A.JH328.10X)

Wireless Kit - Instashow WDC10 (9H.JF878.N4X)

OSD

On Screen Display Language: Arabic/ Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/ Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese (28 languages) □

#### Environmental Notice

\* The Contrast is measure by Full On Full Off standard.

\* LightSource life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice.

\* Storage: Temperature: -20~60°C; Humidity: 10~90%RH (without condensation)

## CECHY PRODUKTU

Model/Seria	<b>MH856UST+ (9H.JKT77.24E)</b>
Technologia	<b>DLP</b>
Rozdzielczość (Podstawowa)	<b>FULL HD</b>
Format Obrazu	<b>16:9</b>
Jasność	<b>3500</b>
Kontrast (...:1)	<b>10000</b>
Źródło Światła	<b>LAMPA</b>
Żywotność Źródła Światła (Ilość Godzin)	<b>5000</b>
Wsp. Powiększenia/Rzutu (Throw Ratio) Minimalny (...:1)	<b>0.33</b>
Wsp. Powiększenia/Rzutu (Throw Ratio) Maksymalny (...:1)	<b>0.33</b>