

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojektacji.pl

CHRISTIE®



Nazwa **Głośnik Christie Cinema surround speaker
LS3S (145-107109-01)**

Cena **0,00 zł**

Producent **Christie**

OPIS PRODUKTU

Crossover : Linear phase, 2-way, passive @ 2.5kHz 12dB/octave, low pass @ 800Hz for bass driver, 6dB/octave

Depth : 228.60 mm

Depth : 9 in

Enclosure :

Vented box alignment

Heavily braced

Height : 500.38 mm

Height : 19.70 in

Impedance : 4 ohm

Input Connectors : 2 position barrier strip

Maximum SPL : 109dB SPL continuous

Sensitivity : 91 dB

Width : 279.40 mm

Width : 11 in

Accessories (optional) :

Christie BKW-SUR wall bracket (fixed)

Allen Products MM-015/016 (adjustable)

Recommended Amplifier Power : 125-250W (FTC) @ 4 ohms

Mounting Options : Wall mounted using 4 x M8 points

Power Handling : 250W (IEC) short term (12dB crest factor) IEC, 12dB crest factor

Power Handling : 125 Watt

System Type : Line source, 2.5-way, passive, vented enclosure

Maximum SPL (Sound Pressure Level) : 121 dB

Driver Components :

1 x 3.5" ribbon driver with Neodymium magnets

2 x 6.5" (mid-bass + bass) paper/Kevlar composite drivers

Coverage Horizontal : 120 degrees

Coverage Vertical : 60 degrees

Warranty (Length/Type) : 5 Years Limited

Construction : 18mm marine plywood

Minimum Frequency Response (Bandwidth) : 70 Hz

Minimum Frequency Response (Bandwidth) : 0.07 kHz

Maximum Frequency Response (Bandwidth) : 20000 Hz

Maximum Frequency Response (Bandwidth) : 20 kHz

Speaker Diameter (Driver) : 88.90 mm

Speaker Diameter (Driver) : 3.50 in

Net Weight : 5.81 kg

Net Weight : 12.80 lbs