

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



CHRISTIE®

Nazwa **Monitor Christie Flat Panel SUHD653-L
(135-042107-01)**

Cena **0,00 zł**

Producent **Christie**

OPIS PRODUKTU

Native resolution

4K UHD 3840 x 2160 (16:9)

Backlight

Edge-lit LED

LED lifespan

30,000 hours to 50% brightness

Display orientation

Landscape

Pixel pitch (WxH)

0.372 x 0.372mm

Bezel size (bottom/side/top)

TBD

Brightness (typical) - (cd/sq m)

450 nits

Contrast ratio (typical)

1,200:1

Viewing angle (CR 10:1)

178 degrees h/v

Refresh rate

60Hz

Response time (typical)

8ms

Color space typical (CIE 1931)

75%

Display colors
10 bit, 1.07 billion

Video inputs
4 x HDMI (Ver 2.0b, HDCP 2.2)
2 x DisplayPort Ver 1.2 (up to 3840 x 2160 @ 60 Hz)

OPS

Video outputs
None

Audio inputs
3.5mm headphone jack

Audio outputs
3.5mm headphone jack

Control inputs
RS-232 via D-Sub9
LAN via RJ45
IR wire extender
USB-A2.0 for service

Power input rating
100-240 VAC @ 50/60Hz

Power consumption
TBD without OPS
TBD maximum without OPS
0.5W standby without OPS

Operating temperature
32-104°F (0-40°C)

Storage temperature
-4-140°F (-20-60°C)

Operating humidity
20-90% RH non-condensing

Physical size (panel only)
(WxHxD): 57.8 x 33.2 x 2.7" (1469 x 844 x 68mm)

Weight
TBD

Mounting
TBD

Runtime
Recommended for 18/7 operation featuring a reliable power supply*

Features
Commercial-grade LCD with edge-lit LED backlight
OPS slot
Anti-glare treatment
2 x 15W speakers
HDMI-CEC
Source switching for failover
No RF capability
4 window multi-source UHD viewing (Quadview, PiP, PBP)

MEMC
Crestron Connected

Accessories
Panel ships with HDMI 2.0 Cable, RS232 Cable, Remote Control with batteries, IR receiver

Warranty
Three years parts and labor limited warranty

*Avoid static images for extended periods. Refer to the user manual for additional runtime guidance. Content and operating conditions can affect the useful life of the product. Please refer to the product

documentation.

Performance specifications are typical. Due to constant research, specifications are subject to change without notice.