

## Inteligentna Elektronika

Ul. Raduńska 36A  
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



**CHRISTIE®**

Nazwa **Monitor Christie Flat Panel SUHD653-L  
(135-042107-01)**

Cena **0,00 zł**

Producent **Christie**

## OPIS PRODUKTU

Native resolution

4K UHD 3840 x 2160 (16:9)

Backlight

Edge-lit LED

LED lifespan

30,000 hours to 50% brightness

Display orientation

Landscape

Pixel pitch (WxH)

0.372 x 0.372mm

Bezel size (bottom/side/top)

TBD

Brightness (typical) - (cd/sq m)

450 nits

Contrast ratio (typical)

1,200:1

Viewing angle (CR 10:1)

178 degrees h/v

Refresh rate

60Hz

Response time (typical)

8ms

Color space typical (CIE 1931)

75%

Display colors  
10 bit, 1.07 billion

Video inputs  
4 x HDMI (Ver 2.0b, HDCP 2.2)  
2 x DisplayPort Ver 1.2 (up to 3840 x 2160 @ 60 Hz)

OPS

Video outputs  
None

Audio inputs  
3.5mm headphone jack

Audio outputs  
3.5mm headphone jack

Control inputs  
RS-232 via D-Sub9  
LAN via RJ45  
IR wire extender  
USB-A2.0 for service

Power input rating  
100-240 VAC @ 50/60Hz

Power consumption  
TBD without OPS  
TBD maximum without OPS  
0.5W standby without OPS

Operating temperature  
32-104°F (0-40°C)

Storage temperature  
-4-140°F (-20-60°C)

Operating humidity  
20-90% RH non-condensing

Physical size (panel only)  
(WxHxD): 57.8 x 33.2 x 2.7" (1469 x 844 x 68mm)

Weight  
TBD

Mounting  
TBD

Runtime  
Recommended for 18/7 operation featuring a reliable power supply\*

Features  
Commercial-grade LCD with edge-lit LED backlight  
OPS slot  
Anti-glare treatment  
2 x 15W speakers  
HDMI-CEC  
Source switching for failover  
No RF capability  
4 window multi-source UHD viewing (Quadview, PiP, PBP)

MEMC  
Crestron Connected

Accessories  
Panel ships with HDMI 2.0 Cable, RS232 Cable, Remote Control with batteries, IR receiver

Warranty  
Three years parts and labor limited warranty

\*Avoid static images for extended periods. Refer to the user manual for additional runtime guidance. Content and operating conditions can affect the useful life of the product. Please refer to the product

documentation.

Performance specifications are typical. Due to constant research, specifications are subject to change without notice.