

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



CHRISTIE®

Nazwa **Monitor Christie Videowall Panel
FHD554-XZ-H (135-033107-01)**

Cena **0,00 zł**

Producent **Christie**

OPIS PRODUKTU

Native resolution

1920 x 1080 (16:9)

Backlight

Direct-lit LED

LED lifespan (50% brightness)

60,000 hrs

Pixel pitch (WxH)

0.63 x 0.63mm

Nominal bezel size

0.88mm combined bezel to bezel

Brightness (typical)

700 nits (cd/sq m)

Contrast ratio (full field)

1200:1 typical

Viewing angle (CR 10:1)

178 degrees h/v

Refresh rate

50-60Hz

Response time (typical)

8ms

Color space typical (CIE 1931)

72%

Display colors

10 bit, 1.07 billion

Display orientation

Portrait and landscape

Signal inputs

2 x HDMI™ (Ver 2.0, HDCP2.2)

2 x DisplayPort™ (Ver 1.2, HDCP2.2)

OPS (HDMI 2.0)

Signal outputs

DisplayPort 1.2 (daisy chains up to 25 panels from one source)

Control inputs

RS-232 via D-Sub9

RJ-45 LAN

Keypad

IR window

IR wire extender

Control outputs

RJ-45 for control looping

Power input rating

100-240 VAC @ 50-60Hz

Power consumption

205 (Typical) without OPS*

280 (Maximum) without OPS*

Standby - $\leq 0.5W$

Operating temperature

32-104°F (0-40°C)

Storage temperature

-4-140°F (-20-60°C)

Operating humidity

20-90% RH non-condensing

Size (without handles)

(W x H x D) 47.6 x 26.8 x 3.75" (1210.5 x 681.2 x 95.3 mm)

Weight (without handles)

62lbs (28kg)

Panel mount locations

VESA (WxH) 400 x 400mm, M8 (15mm internal depth)

Runtime

Designed for 24/7 operation** featuring a reliable power supply and cooling system

Features

Commercial-grade LCD with LED backlight

Standard size OPS

Christie Phoenix EP supported***

Built-in processing supports video walls up to 10x10

Anti-glare coating

Video Wall Toolbox software

SNMP for monitoring

Multi-stream transport supported across up to four panels (UHD at 60fps)

Remote and button lock

Pixel Orbiting (IRFM)

Bezel compensation

Kensington lock

Accessories (Included)

Panel ships with DisplayPort cable

IR remote control

External IR receiver

Power cable

Control daisy chain cable

Spacer tool

Safety guide

Accessories (Optional)

MPL15 landscape/portrait capable LCD video wall mount

ML25 6-axis landscape mount for mounting depth of $\leq 4"$ (100mm)

Warranty

Three years parts and labor limited warranty

*OPS device consumption is not considered.

**Avoid static images for extended periods. Refer to the user manual for additional runtime guidance.

***Available soon.

Content and operating conditions can affect the useful life of the product. Please refer to the product documentation and Christie Operating Guidelines for Flat Panels.