

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



CHRISTIE®

Nazwa **Monitor Christie Videowall Panel
FHD554-XZ-HR (135-032106-01)**

Cena **0,00 zł**

Producent **Christie**

OPIS PRODUKTU

Native resolution

1920 x 1080 (16:9)

Backlight

Direct-lit LED

LED lifespan (50% brightness)

60,000 hrs

Pixel pitch (WxH)

0.63 x 0.63mm

Nominal bezel size

0.88mm combined bezel to bezel

Brightness (typical)

700 nits (cd/sq m)

Contrast ratio (full field)

1200:1 typical

Viewing angle (CR 10:1)

178 degrees h/v

Refresh rate

50-60Hz

Response time (typical)

8ms

Color space typical (CIE 1931)

72%

Display colors

10 bit, 1.07 billion

Display orientation

Portrait and landscape

Signal inputs

2 x HDMI™ (Ver 2.0, HDCP2.2)

2 x DisplayPort™ (Ver 1.2, HDCP2.2)
OPS (HDMI 2.0)
Signal outputs
DisplayPort 1.2 (daisy chains up to 25 panels from one source)
Control inputs
RS-232 via D-Sub9
RJ-45 LAN
Keypad
IR window
IR wire extender
Control outputs
RJ-45 for control looping
Power input rating
100-240 VAC @ 50-60Hz
Power consumption
205 (Typical) without OPS*
265 (Maximum) without OPS*
Standby - ≤0.5W without OPS*
Operating temperature
32-104°F (0-40°C)
Storage temperature
-4-140°F (-20-60°C)
Operating humidity
20-90% RH non-condensing
Size (without handles)
(W x H x D) 47.6 x 26.8 x 3.75" (1210.5 x 681.2 x 95.3 mm)
Weight (without handles)
62lbs (28kg)
Panel mount locations
VESA (WxH) 400 x 400mm, M8 (15mm internal depth)
Runtime
Designed for 24/7 operation** featuring a reliable power supply and cooling system
Features
Commercial-grade LCD with LED backlight
Standard size OPS
Christie Phoenix EP supported***
Built-in processing supports video walls up to 10x10
Anti-glare coating
Video Wall Toolbox software
SNMP for monitoring
Multi-stream transport supported across up to four panels (UHD at 60fps)
Remote and button lock
Pixel Orbiting (IRFM)
Bezel compensation
Kensington lock
Accessories (Included)
Panel ships with DisplayPort cable
IR remote control
External IR receiver
Power cable
Control daisy chain cable
Spacer tool
Safety guide
Accessories (Optional)
MPL15 landscape/portrait capable LCD video wall mount

ML25 6-axis landscape mount for mounting depth of ≤ 4 "(100mm)

Remote Power Supply Rectifier

Remote Power Supply Shelf

DC Power Cables

Warranty

Three years parts and labor limited warranty

*OPS device consumption is not considered.

**Avoid static images for extended periods. Refer to the user manual for additional runtime guidance.

***Available soon.

Content and operating conditions can affect the useful life of the product. Please refer to the product documentation and Christie Operating Guidelines for Flat Panels.