## **Inteligentna Elektronika** Ul. Raduńska 36A 83-333 Chmielno

Tel.: +48 730 90 60 90 E-mail: info@centrumprojekcji.pl



CHKISTIE	
Nazwa	Monitor Christie Videowall Panel FHD554-XZ-HR (135-032106-01)
Cena	0,00 zł
Producent	Christie

## **OPIS PRODUKTU**

Native resolution 1920 x 1080 (16:9) Backlight Direct-lit LED LED lifespan (50% brightness) 60,000 hrs Pixel pitch (WxH) 0.63 x 0.63mm Nominal bezel size 0.88mm combined bezel to bezel Brightness (typical) 700 nits (cd/sq m) Contrast ratio (full field) 1200:1 typical Viewing angle (CR 10:1) 178 degrees h/v Refresh rate 50-60Hz Response time (typical) 8ms Color space typical (CIE 1931) 72% **Display colors** 10 bit, 1.07 billion Display orientation Portrait and landscape Signal inputs 2 x HDMI<sup>™</sup> (Ver 2.0, HDCP2.2)

2 x DisplayPort<sup>™</sup> (Ver 1.2, HDCP2.2) **OPS (HDMI 2.0)** Signal outputs DisplayPort 1.2 (daisy chains up to 25 panels from one source) **Control** inputs RS-232 via D-Sub9 RI-45 LAN Keypad **IR** window IR wire extender **Control outputs** RJ-45 for control looping Power input rating 100-240 VAC @ 50-60Hz Power consumption 205 (Typical) without OPS\* 265 (Maximum) without OPS\* Standby - ≤0.5W without OPS\* Operating temperature 32-104°F (0-40°C) Storage temperature -4-140°F (-20-60°C) **Operating humidity** 20-90% RH non-condensing Size (without handles) (W x H x D) 47.6 x 26.8 x 3.75" (1210.5 x 681.2 x 95.3 mm) Weight (without handles) 62lbs (28kg) Panel mount locations VESA (WxH) 400 x 400mm, M8 (15mm internal depth) Runtime Designed for 24/7 operation\*\* featuring a reliable power supply and cooling system Features Commercial-grade LCD with LED backlight Standard size OPS Christie Phoenix EP supported\*\*\* Built-in processing supports video walls up to 10x10 Anti-glare coating Video Wall Toolbox software SNMP for monitoring Multi-stream transport supported across up to four panels (UHD at 60fps) Remote and button lock Pixel Orbiting (IRFM) Bezel compensation **Kensington lock** Accessories (Included) Panel ships with DisplayPort cable IR remote control External IR receiver Power cable Control daisy chain cable Spacer tool Safety guide Accessories (Optional) MPL15 landscape/portrait capable LCD video wall mount

ML25 6-axis landscape mount for mounting depth of <= 4"(100mm) Remote Power Supply Rectifier Remote Power Supply Shelf DC Power Cables Warranty Three years parts and labor limited warranty \*OPS device consumption is not considered. \*\*Avoid static images for extended periods. Refer to the user manual for additional runtime guidance. \*\*\*Available soon. Content and operating conditions can affect the useful life of the product. Please refer to the product documentation and Christie Operating Guidelines for Flat Panels.