

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl

CHRISTIE®



Nazwa **Procesor audio i wideo Christie SKA-3D
108-446105-XX**

Cena **0,00 zł**

Producent **Christie**

OPIS PRODUKTU

Height

3.5" (2 Rack Units) 4" with feet (88.9mm or 101.6mm with feet)

Width

19" (482.6mm)

Length

12" (304.8mm)

Weight

16lbs (7.3kg)

Power

100V to 240V AC 50/60Hz, 100W

Inputs

Video

2 x HDMI • 1 x HDMI / DVI-I

1 x HDMI / DVI-D (Support for HDCP and embedded audio)

2 x Component (3 x RCA)

VGA (HD15)

Audio

16 x DCI-AES Digital, 8 Pairs (DB-25)

DCI-AES ALT1 Pairs 1-4 (RJ-45)

DCI-AES ALT2 Pairs 5-8 (RJ-45)

8 x Balanced analog (DB-25)

3 x Analog (RCA)

3 x Coax SPDIF (RCA)

3 x Optical SPDIF (Toslink)

2 x HDMI (Support for embedded audio)

Microphone (XLR)

Outputs

Video

HDMI L / DVI-D (Left eye in dual stream 3D mode)
HDMI R / DVI-D (Right eye in dual stream 3D mode)

Audio

8 x Balanced analog (DB-25)

L (Left) Low, balanced analog, (3 pin Phoenix)

C (Center) Low, balanced analog, (3 pin Phoenix)

R (Right) Low, balanced analog, (3 pin Phoenix)

Aux 1 / LS (Left Surround) Low, balanced analog, (3 pin Phoenix)

Aux 2 / RS (Right Surround) Low, balanced analog, (3 pin Phoenix)

HI (Hearing Impaired), balanced analog, (3 pin Phoenix)

VI/N (Visually Impaired/Narrative), balanced analog, (3 pin Phoenix)

Booth monitor, unbalanced analog (RCA)

Headphone (TRS)

Control and network ports

Ethernet (RJ-45) for IP control and setup

RS-232 (DB-9)

8 contact closure inputs (16 pin Phoenix)

4 dry relay outputs (8 pin Phoenix)

Supported formats

Video

Up to 1080p/2K 60Hz

Audio

Digital PCM, up to 16 channels

Balanced analog +4db, up to 8 channels

Dolby Digital

Dolby Digital Plus

Dolby TrueHD

DTS

DTS-HD

DTS-HD Master Audio

Unbalanced analog -10db, Stereo

Microphone, balanced