

## Inteligentna Elektronika

Ul. Raduńska 36A  
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl

**CHRISTIE®**



Nazwa **Wyświetlacz Christie UHD651-L  
(135-018100-02)**

Cena **0,00 zł**

Producent **Christie**

## OPIS PRODUKTU

Screen size (diagonal)

65"/165.1cm

Native resolution

4K UHD 3840 x 2160 (16:9)

Backlight

Direct-lit LED

LED lifespan

50,000 hours to 50% brightness

Display orientation

Landscape

Pixel pitch

0.372 x 0.372mm

Nominal bezel size

21mm/15mm/15mm

(bottom/side/top)

Brightness

400 nits (cd/m<sup>2</sup>) typical

Contrast ratio (full field)

4000:1 typical

Viewing angle (CR 10:1)

178° h/v

Refresh rate

60Hz  
Response time  
8ms typical  
Color space (CIE 1931)  
75% typical  
Display colors  
8 bit, 16.7 million colors  
Video inputs  
2 x HDMI (Ver 2.0, HDCP 2.2)  
DisplayPort (Ver 1.2a, HDCP 1.3)  
VGA  
YPbPr  
2 x USB 2.0  
USB 3.0  
Video outputs  
DisplayPort 1.2a  
HDMI 2.0  
Audio inputs  
RCA (L/R) line in  
Audio outputs  
RCA (L/R) line out  
3.5mm headphone jack  
SPDIF coax  
Control inputs  
RS-232 (D-Sub9)  
LAN (RJ45)  
IR wire extender  
Power input rating  
100-240 VAC @ 50-60Hz  
Power consumption  
73W typical without OPS  
140W maximum without OPS  
≤0.5W in standby without OPS  
Operating temperature  
32-104°F (0-40°C)  
Storage temperature  
-4-140°F (-20-60°C)  
Operating humidity  
20-90% RH non-condensing  
Physical size  
(panel only)  
(WxHxD) 57.4 x 33.1 x 3.8"  
(1459 x 841 x 96mm)  
Physical weight  
49.6lbs (22.5kg)  
Mounting  
VESA 400 x 400mm, M6  
Runtime  
Designed for 16/7 operation featuring a reliable power supply1  
Features  
Commercial grade LCD with LED backlight  
OPS slot  
Anti-glare treatment  
2 x 8W speakers  
On/off scheduler

USB playback of Photo/Video/MP3

HDMI-CEC

Source switching for failover

Kensington lock

Wi-Fi®

Bluetooth

Miracast device connectivity

Pixel shifting

Accessories

Panel ships with IR remote control

External IR receiver

Power cable

User manual

Optional TA651 up to 10 point IR touch overlay

Warranty

Three year parts and labor limited warranty

Contact an authorized Christie representative for full details

1 Avoid static images for extended periods. Refer to the user manual for additional runtime guidelines.

Content and operating conditions can affect the useful life of the product. Please refer to the product user manual and Christie Operating Guidelines for Flat Panels.