

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl

CHRISTIE®



Nazwa **Wyświetlacz Christie UHD651-L
(135-018100-02)**

Cena **0,00 zł**

Producent **Christie**

OPIS PRODUKTU

Screen size (diagonal)

65"/165.1cm

Native resolution

4K UHD 3840 x 2160 (16:9)

Backlight

Direct-lit LED

LED lifespan

50,000 hours to 50% brightness

Display orientation

Landscape

Pixel pitch

0.372 x 0.372mm

Nominal bezel size

21mm/15mm/15mm

(bottom/side/top)

Brightness

400 nits (cd/m²) typical

Contrast ratio (full field)

4000:1 typical

Viewing angle (CR 10:1)

178° h/v

Refresh rate

60Hz
Response time
8ms typical
Color space (CIE 1931)
75% typical
Display colors
8 bit, 16.7 million colors
Video inputs
2 x HDMI (Ver 2.0, HDCP 2.2)
DisplayPort (Ver 1.2a, HDCP 1.3)
VGA
YPbPr
2 x USB 2.0
USB 3.0
Video outputs
DisplayPort 1.2a
HDMI 2.0
Audio inputs
RCA (L/R) line in
Audio outputs
RCA (L/R) line out
3.5mm headphone jack
SPDIF coax
Control inputs
RS-232 (D-Sub9)
LAN (RJ45)
IR wire extender
Power input rating
100-240 VAC @ 50-60Hz
Power consumption
73W typical without OPS
140W maximum without OPS
≤0.5W in standby without OPS
Operating temperature
32-104°F (0-40°C)
Storage temperature
-4-140°F (-20-60°C)
Operating humidity
20-90% RH non-condensing
Physical size
(panel only)
(WxHxD) 57.4 x 33.1 x 3.8"
(1459 x 841 x 96mm)
Physical weight
49.6lbs (22.5kg)
Mounting
VESA 400 x 400mm, M6
Runtime
Designed for 16/7 operation featuring a reliable power supply1
Features
Commercial grade LCD with LED backlight
OPS slot
Anti-glare treatment
2 x 8W speakers
On/off scheduler

USB playback of Photo/Video/MP3

HDMI-CEC

Source switching for failover

Kensington lock

Wi-Fi®

Bluetooth

Miracast device connectivity

Pixel shifting

Accessories

Panel ships with IR remote control

External IR receiver

Power cable

User manual

Optional TA651 up to 10 point IR touch overlay

Warranty

Three year parts and labor limited warranty

Contact an authorized Christie representative for full details

1 Avoid static images for extended periods. Refer to the user manual for additional runtime guidelines.

Content and operating conditions can affect the useful life of the product. Please refer to the product user manual and Christie Operating Guidelines for Flat Panels.