

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



EIKI
Projectors ... and more!

Nazwa **Projektor EIKI EK-307W**

Cena **0,00 zł**

Producent **EIKI**

OPIS PRODUKTU

Display Type 0.59" 3LCD

Resolution WXGA (1280 x 800)

Aspect Ratio 16:10

Brightness (ANSI) 5,100 lm

Contrast Ratio 10,000:1

Projection Light Source 280 W x 1

Light Source Life 4,000 / 3,000 hrs (Eco / Normal)

Image Diagonal 30" - 300"

Lens (F Value / Focal length) F = 1.6 - 1.9 f = 15.31 - 24.64 mm

Zoom Ratio Manual x 1.6

Throw Distance 0.74 - 12.37 m

Throw Ratio 1.16 - 1.89 : 1

Lens Shift V: +/- 45%, H: +/- 10% (Manual)

Keystone Correction V: +/- 30 degrees, H: +/- 15 degrees, Corner Correction

Projection Elevation Adjustment Up to 10 degrees

Scanning Frequency H Sync: 15 - 100 kHz, V sync: 48 - 85 Hz

Dot Clock 160 MHz

Input Signals - Computer WUXGA (1920 x 1200) - VGA (640 x 480)

Input Signals - Video 1080i/p, 720p, 576i/p, 480i/p

Terminal

HDMI In HDMI x 2 (1 HDMI supports MHL)

VGA In D-Sub 15 x 2

YPbPr (Component) D-Sub 15 x 1 (Shared with VGA IN 1 / S-Video)

Video (Composite) RCA x 1

S-Video D-sub 15 x 1 (Shared with VGA IN 1 / Component)

USB USB Type A x 1*1, USB Type B x 1*2

Monitor Out (VGA Out) D-Sub 15 x 1 (Shared with VGA 2)

Audio In RCA x 2 (L/R), 3.5mm Mini Jack x 1

Audio Out 3.5mm Mini Jack x 1

LAN RJ45 x 1

RS-232 CD-sub 9 x 1

Built-in Speaker Mono 10.0 W x 1
Fan Noise (Eco / Normal) 33.5 dB / 40.0 dB
Dimensions (W x H x D) 395 x 128 x 318 mm
Weight 4.45 kg
Power Requirements AC 100 - 240 V, 50/60 Hz
Power Consumption 345W(Normal), <0.5W(Standby), <3.0W(Lan control Standby)
Thermal Dissipation 1,177 BTU

CECHY PRODUKTU

Model/Seria	EK-307W
Technologia	LCD
Rozdzielczość (Podstawowa)	WXGA
Format Obrazu	16:10
Jasność	5100
Kontrast (...:1)	10000
Źródło Światła	LAMPA
Żywotność Źródła Światła (Ilość Godzin)	3000
Wsp. Powiększenia/Rzutu (Throw Ratio) Minimalny (...:1)	1.16
Wsp. Powiększenia/Rzutu (Throw Ratio) Maksymalny (...:1)	1.89