

## Inteligentna Elektronika

Ul. Raduńska 36A  
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



Nazwa **Projektor Eiki EK-612X**

Cena **0,00 zł**

Producent **EIKI**

## OPIS PRODUKTU

Podstawowe parametry: XGA, DLP, 7000 ANSI LM, 4400:1, 1500/2000h (eco), DVI-D, D-Sub 15pin, HDMI, HDBaseT, Component Video 3xRCA, Composite Video, remote in Mini Jack, Monitor out, RS232, LAN RJ45, USB Typ A for W iFi Dongle, Mini USB Typ B (service), LENS SHIFT pionowy +/-50%, poziomy +/-15%, Keystone pionowy +/-20 stopni, poziomy +/-20 stopni, 14 kg, Brightness 7,000 ANSI Lumens Contrast Ratio 4400:1 Resolution and Aspect Ratio XGA (1024x768), 4:3 Color Reproduction 24-bit (16.7 million colors) Projection Lamp 465 Watts UHP Estimated Lamp Life (Eco / Normal) 2,000 / 1,500 hours Total Pixels 7,864,32 (1024x768) x 1 Imaging System 0.7" DMD™ DLP® chip x 1 Scanning Frequency Auto: H Sync. 15-91 kHz, V Sync. 24-85 Hz Pixel Clock 1up-to 150 MHz Lens Optional Lenses Available Lens Specs Optional Lenses Available Lens Ratios Optional Lenses Available Image Diagonal 50-300 in (127-762 cm) Image Width 3.3-20 ft (1.0-6.1 m) Throw Distance 4.19-31.5 ft (1.28-9.63 m) Projector Elevation Adjustment (legs) up-to 10° Maximum Pitch Up-to 360° Installation Vertical Keystone Correction Digital: up-to 30° Up or Down Horizontal Keystone Correction Digital: up-to 30° Left or Right Image Orientation Normal, Reversed, Inverted Local Control / Power Management Full Function / Auto Shutdown Remote Control MiniStereo x 1 RS-232 Control Dsub9 x 1 LAN Port RJ45 x 1 Computer Input in Pixels up-to 1600x1200 (4:3), 1920x1200 (16:10) Analog 4x3 Inputs UXGA, SXGA+, SXGA, XGA, SVGA, VGA, MAC Analog Wide Inputs WUXGA, WSXGA+, WXGA+, WXGA Digital 4x3 Inputs UXGA, SXGA+, SXGA, XGA, SVGA, VGA, MAC Digital Wide Inputs WUXGA, WSXGA+, WXGA+, WXGA Video Formats NTSC / PAL / SECAM Video Input Analog 480i/p, 576i/p Video Input Digital 480p, 575p, 720p, 1080i/p Image Signal Resizing Smart Scaling Technology Image Signal Inputs Computer 1 Dsub15 x 1 Digital Video (w/ HDCP) HDMI x 1 Digital Video (w/ HDCP) DVI-D x 1 HDBaseT RJ45 x 1 Component Video (Y,Pb,Pr and R/G/B) RCA x 3 Composite Video RCA x 1 USB Type A - Wifi Dongle Type A x 1 Mini USB - Service Mini USB x 1 Composite Video RCA x 1 Fan Noise (Eco / Normal) 37 dB / 41 dB Cabinet

Size (HxWxD) - excluding legs 8.1 x 17.8 x 15.3 in (20.5 x 45.2 x 38.8 cm) Weight (without lens) 30.8 lb (14 kg) Packaged Size (HxWxD) TBA Packaged Weight 38.1 lb (17.3 kg) Operating Temperature 41-95°F (5-35°C) Electrical Safety Compliance IEC / UL / cUL Electromagnetic Compatibility FCC Class A, CE Mark Power Requirements 100-240V AC, 50/60 Hz Power Consumption 0.5 W in Eco Standby mode, up-to 580 W Heat up-to 1,978 BTU/hr Security Facilities Security Bar, Kensington® Security Slot UPC 4571194678154 Limited Warranty: to the original end use customer only Projector: 3 years / 6000 hours (whichever occurs first) Lamp: 1 year ownership / 500 hours (whichever occurs first)

## CECHY PRODUKTU

Model/Seria	<b>EK-612X</b>
Technologia	<b>DLP</b>
Rozdzielczość (Podstawowa)	<b>XGA</b>
Format Obrazu	<b>4:3</b>
Jasność	<b>7000</b>
Kontrast (...:1)	<b>4400</b>
Źródło Światła	<b>LAMPA</b>
Żywotność Źródła Światła (Ilość Godzin)	<b>1500</b>
Wsp. Powiększenia/Rzutu (Throw Ratio) Minimalny (...:1)	<b>0.78</b>
Wsp. Powiększenia/Rzutu (Throw Ratio) Maksymalny (...:1)	<b>5.7</b>