

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



Nazwa **Projektor EIKI LC-XB250A**

Cena **6 568,00 zł**

Producent **EIKI**

OPIS PRODUKTU

Parametry techniczne

Brightness:

4000 ANSI Lumens

Contrast Ratio:

2000 : 1

Illumination Uniformity (corner to center):

85%

Resolution and Aspect Ratio:

1024 x 768 XGA

Color Reproduction:

8 bit

Projection Lamp:

245 Watt UHP

Estimated Lamp Life:

up to 5000 hours of use

Imaging System:

0,63" Inorganic PolySilicon active matrix TFT panels x 3

Total Pixels:

2,359,296 ((1024 x 768) x 3)

Pixel Clock:

up to 140 MHz

Lens Type:

Manual zoom and focus

Lens specifications:

f = 15,5 - 24,5mm

Lens ratios:

zoom max:min: 1.6:1, throw:width: 1.18-1.91:1

Image Diagonal:

76 - 762 cm

Image Width:

0,61 - 6,1 m

Throw Distance:

0,7 - 7,2 m

Projector Elevation Adjustment (legs):

up to 12° up

Maximum Pitch:

up to 30° up or down

Vertical Keystone Correction:

Digital: up to 30° up or down

Image Orientation:

normal, reversed, inverted

Local Control / Power Management:

full function / auto shutdown

RS232 Controls Ports (In & Out):

Dsub 9 pin x 1

Remote Projector Control:

Wireless (infra red) x 1

LAN Port:

RJ-45 x 1

Computer Native Resolution:

computer input in pixels: up to 1600 x 1200 (4:3), 1920 x 1200 (16:10)

Computer Compatibility (formats):

UXGA, SXGA+, SXGA, XGA, SVGA, VGA, MAC, WUXGA, WSXGA+, WXGA+, WXGA,

Video Compatibility (formats):

NTSC, PAL, SECAM, NTSC 4.43, PAL-M, PAL-N

Other Inputs and Outputs:

Image signal inputs: COMPUTER Analog / COMPONENT (with optional adapter) Dsub15 x 1

COMPUTER Digital and Analog / Digital Video DVI-I x 1 S-Video IN S-Video x 1 Composite video

..... RCA x 1 Audio signal inputs: COMPUTER AUDIO IN 1and2 / Microphone ... Stereo:MiniStereo x 2 for

inputs 3 and 4 Stereo: RCA x 2 Outputs: Computer Monitor Dsub15 x 1 Audio output

Variable, Stereo: MiniStereo x 1

Image Signal Resizing:

Smart scaling technology

Fan Noise:

as low as 29 dBA

Cabinet Size (HxWxD):

87,5 x 350 x 254 mm

Weight:

3,4 kg

Packaged Size (HxWxD):

198 x 434 x 406 mm

Packaged Weight:

5,9 kg

Power Requirements:

100 - 240 V AC, 50/60 Hz

Power Consumption:

0,5 W (Standby Eco) up to 322Watts

Heat:

up to 1179 BTU

Electrical Safety Compliance:

UL, cUL, IEC

Electromagnetic Compatibility:

FCC, Class B, CE Mark

Security Facilities:

Kensington Security Slot

Operating Temperature:

5 - 35°C

User Maintenance:

clean air filter, replace lamp

Included Accessories:

Quick start guice, Owner's manual on CD-ROM, power cord, VGA computer input cable (Dsub15 to Dsub15), wireless remote control and batteries (AAA x 2), network software on CD-ROM, soft carry bag, lens cover, filter cover for ceiling.

CECHY PRODUKTU

Model/Seria	LC-XB250A
Technologia	LCD
Rozdzielczość (Podstawowa)	XGA
Format Obrazu	4:3
Jasność	4000
Kontrast (...:1)	2000
Źródło Światła	LAMPA
Żywotność Źródła Światła (Ilość Godzin)	5000
Wsp. Powiększenia/Rzutu (Throw Ratio) Minimalny (...:1)	1.18
Wsp. Powiększenia/Rzutu (Throw Ratio) Maksymalny (...:1)	1.91