

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



EIKI
Projectors ... and more!

Nazwa **Uniwersalny uchwyt sufitowy EIKI
Universal Ceiling Mount (0173-4293)**

Cena **0,00 zł**

Producent **EIKI**

OPIS PRODUKTU

Model: 0173-4293

Roll Adjustment

+/- 4 degrees adjustment up or down. Loosen screw, adjust mount and tighten screw to hold adjustment.

Pitch Adjustment

+/- 25 degrees adjustment on each side of the mount. Loosen screw, adjust mount and tighten screw to hold adjustment. Full range of pitch in a flush mount installation.

Yaw Adjustment

360 degrees by turning the mount on the threaded column and securing in place with set screw. 12 degrees yaw possible on flush mount using slots in top mount.

Color

Black, Silver or White

Column

1.5" NPT

Weight Capacity

50 lbs.

Three Mounting Methods

1. Flush mount to suitable ceilings using the four corner slots in top of the mount. The mount allows you to flush mount without disassembly by providing suitable access for screwdrivers and socket sets. ±25 degrees of pitch when flush mounted. 12 degrees yaw possible on flush mount with slots in top of the mount (Hardware not included).

2. 1/4" Threaded Rod using the four corner slots in the top of the mount. (Threaded Rod not included.)

3. 1 1/2" NPT Threaded Extension Column using the threaded opening at the top of the ceiling mount. (Threaded Extension Column not included.)

Convenient Lamp and Filter Access

Projector bracket provides needed access for: quick lamp changes, easy filter cleaning and proper projector ventilation.

Quick Projector Disconnect/Reconnect

To quickly and easily remove the projector from the ceiling: loosen thumbnuts connecting the bracket to the universal top. Remove projector and bracket from top. The top retains the registration adjustments. This feature makes projector servicing and maintenance quick and easy by eliminating the need for re-registration. Security wrench included for use when thumbnuts are replaced with All-Points™ Security System hardware.

Lateral Shift Accessory

Often times ceiling structures will not allow the projector to be mounted in exact alignment with the projection screen. The Lateral Shift Accessory saves an abundance of time and hassles in trying to solve this common problem. It allows the projector to be shifted three inches right or left of the installation spot (5 3/4 inches on projectors under 15 lbs.). Easily accommodate different lens placement when projectors are replaced in existing installations and maintains quick disconnect feature. Includes All-Points™ Security System hardware.