

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



HITACHI
Inspire the Next

Nazwa **Projektor Hitach CP-EX3051WN**

Cena **2 568,00 zł**

Producent **Hitachi**

OPIS PRODUKTU

Dane techniczne

Display

Projection Technology 3LCD, 3 chip technology

Resolution XGA - 1024 x 768

White Light Output 3,300 ANSI lumens

Color Light Output 3,300 ANSI lumens

Colors 16.7 million colors

Aspect Ratio Native 4:3 and 16:9 / 16:10 / 14:9 / zoom compatible

Contrast Ratio 20,000 : 1 (using active IRIS)

Throw Ratio

(distance : width)

1.5 - 1.8 : 1

Focus Distance 33" - 427"

Display Size 30" - 300"

Lens & Operation

Lens f = 19 - 23 mm, x 1.2 manual zoom and focus

Lamp Wattage 230W

Expected Lamp Life* Approximately 6,000 hours (standard mode)

12,500 hours (eco mode)

Expected Filter Life** Approximately 10,000 hours

Speaker Output 16W

Keystone H and V: +/- 30°

Compatibility

Computer VGA, SVGA, XGA, WXGA, SXGA/SXGA+/HD/UXGA (compressed),

Mac 16"

H-Sync 15 kHz - 106 kHz

V-Sync 56 Hz - 120 Hz

Composite Video NTSC, NTSC4.43, PAL, PAL-M, -N, SECAM

Component Video 480i, 480p, 576i, 576p, 720p, 1080i, 1080p

HDMI 480i, 480p, 576i, 576p, 720p, 1080i, 1080p

Computer signal TMDS Clock 25 MHz - 162 MHz

Connectors

Digital Input HDMI x 2 (HDCP compliant)

Computer Input 1 15-pin mini D-sub x 1 (shared with analog component video input)

Computer Input 2 15-pin mini D-sub x 1 (shared with analog component video input and monitor out)

Computer Monitor Output 15-pin mini D-sub x 1 (shared with computer in 2 and analog component video input)

Video Input

Composite Video RCA jack x 1

Component Video 15-pin mini D-sub x 2 (shared with computer in 1, in 2/monitor out)

Audio Input 3.5 mm stereo mini jack x 2, RCA jack (L/R) x 1

Audio Output 3.5mm stereo mini jack x 1

Network LAN Wired RJ-45 port (10 base-T/100 base-TX)

Network LAN Wireless USB-A, IEEE802.11 a/b/g/n/ac - optional wireless adapter required

USB Type A x 1 (PC-less presentation or wireless adapter)

Type B x 1 (Remote control mouse or PC screen display)

Control Terminals 9-pin D-sub x 1 (RS-232 control)

Ratings & Warranty

Power Supply AC100-120V / AC220-240V, 50/60Hz

Power Consumption 320W / 310W

Operating Temperature 32°F - 95°F (0°C - 35°C)

Dimensions (W x D x H) 13.7" x 10.4" x 3.5" (excluding protrusions)

Weight Approximately 7.9 lbs.

Approvals UL 60950-1 / cUL FCC Part 15 subpart B class B

Warranty 3 years limited parts and labor

5 years or 10,000 hours light source