

## Inteligentna Elektronika

Ul. Raduńska 36A  
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



**HITACHI**  
Inspire the Next

Nazwa **Zestaw interaktywny Hitachi SBM680 / CX251**

Cena **0,00 zł**

Producent **Hitachi**

## OPIS PRODUKTU

SBM680

Dimensions and weights

Screen Size 195.6 cm (77") Diagonal

Aspect Ratio 4:3

Weight 18.5 kg (40 lb. 13 oz.)

Shipping dimensions 181 cm W × 134.6 cm H × 11.4 cm D  
(71 1/4" × 53" × 4 1/2")

Shipping weight 23.6 kg (52 lb.)

Temperature specifications

Storage -20°C to 50°C (-4°F to 122°F)

Operation 5°C to 35°C (41°F to 95°F) with up to 80% humidity, non-condensing

Others

Digitizing technology Four-camera DVIT

Frame finish White and light gray (approximates PANTONE® Cool Gray 4C)

Power requirements 1.8 m (6') power cable. Power consumption is less than 7 W (100V to 240V AC, 50/60 Hz, 5V DC 2.0A).

Computer connection Includes a 5m (16') USB 2.0 cable to connect to the room computer. Your SMART Board M680 interactive whiteboard supports one computer connection on a primary display only.

Certification and compliance

Regulatory certification CSA (U.S./Canada)

Environmental compliance

China EIP

European Union REACH, RoHS, WEEE, Packaging and ErP Standby

U.S. Packaging and Conflict Minerals

Purchasing information (Order numbers)

SBM680 195.6 cm (77") diagonal SMART Board M680 interactive whiteboard with an active pen tray.

Includes a SMART Notebook software installation DVD.

SBM680-B Bulk order of 10 SBM680 units

Warranty Two-year limited equipment warranty

CX251

Parametry optyczne

Standard VGA XGA

Rozdzielczość 1024×768

Jasność 2500

Jasność ECO 1700

Kontrast 2000:1

Wielkość ekranu 60" ~150"

Korekta efektu trapezowego Automatyczna w pionie

Moc lampy 225W

Gniazda

Wejścia komputerowe 2 x 15-pin Mini D-sub

Wyjścia komputerowe 1 x 15-pin Mini D-sub

Wejścia video

1 x HDMI

1 x RCA (Composite Video),

1 x S-Video,

2 x Component poprzez wejście komputerowe (15-pin Mini D-sub)

Wejścia audio 1 x RCA (L/P)

Wyjścia audio 1 x RCA (L/P)

Sterowanie 1 x 9-pin D-sub RS-232C

Wejścia USB Typu B Mini

Parametry fizyczne

Głośniki 1x 1W

Waga 3,4 kg

Głośność 37dBdB (tryb Normal) / 30dBdB (tryb Eco)

Wymiary (bez nóżek i obiektywu) Długość: 303mm / Wysokość: 85mm / Szerokość: 345mm