

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



Nazwa **Monitor dotykowy LG Ultra HD Interactive Digital Board 86TR3D**

Cena **71 340,00 zł**

Producent **LG**

OPIS PRODUKTU

PANEL

Screen Size

86"

Panel Technology

IPS

Aspect Ratio

16 : 9

Brightness

410 cd/m2 *

Viewing Angle(H x V)

178 x 178

Response Time

8 ms (G to G)

Surface Treatment

Low Haze 3%

CONNECTIVITY

Input

HDMI (3), DP, DVI-D, RGB, Audio in, USB 3.0, USB 2.0, OPS USB 2.0

Output

Touch USB 2.0 (2)

External Control

RS232C, RJ45

PHYSICAL SPECIFICATION

Bezel Color

Black

Bezel Width

50.7 mm (T/L/R), 62.2 mm (B)

Monitor Dimension (W x H x D)

79.8" x 46.5" x 3.8"

Weight (Head)

204.5 lbs

Carton Dimensions (W x H x D)

86.2" x 57.9" x 14.6"

Packed Weight

267.2 lbs

Handle

Yes

VESA™ Standard Mount Interface

600 mm x 400 mm

SPECIAL FEATURES

Yes

Temperature Sensor, Auto Brightness Sensor, ISM method, DPM Select, Brightness Control, PM Mode, Reader Mode, Crestron SDK, Wake on LAN, Energy Saving, File Play with USB, 2 PIP/PBP, Internal Memory (64GB), Wi-Fi (802.11n Combo built-in), USB Cloning, Failover, No Signal Image, Mirroring, Soft AP, BEACON

ENVIRONMENT CONDITIONS

Operation Temperature Range

32 °F to 104 °F

Operation Humidity Range

10% to 80%

POWER

Power Supply

100-240V~, 50/60Hz

Power Type

Built-in Power

Power Consumption Typ.

Under 330 W

Power Consumption-Smart Energy Saving on

Under 200 W

STANDARD (CERTIFICATION)

Safety

UL / cUL / CB / TUV / KC

EMC

FCC Class "A" / CE / KCC

ErP / Energy Star

NA

MEDIA PLAYER COMPATIBILITY

OPS Type Compatible

Yes

External Media player Attachable

No

SOFTWARE COMPATIBILITY

Content Management Software

SuperSign Premium

Control and Monitoring Software

SuperSign Link

EMBEDDED COLLABORATION AND WRITING SOFTWARE

Yes

SuperSign IDB

ACCESSORY

Basic

Remote Controller (include battery 2ea), Power Cord, QSG, HDMI (3M), Regulation Book, Phone to RS232C Gender, Touch Pen (2ea), Eyebolt (2ea)

Optional

OPS Kit (KT-OPSA), LSW640A/B (Wall Mount)

TOUCH SPECIFICATIONS

Touch type

InGlass™**

Available object size for touch

more than Ø 3 mm

Accuracy

2 mm + 0.2 mm

Interface

USB 2.0

Protection Glass Thickness

4T (Anti-Glare)

Multi touch point

Max 20 Point