

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



Nazwa **Monitor Dotykowy LG 27TNF3K**

Cena **0,00 zł**

Producent **LG**

OPIS PRODUKTU

PANEL

Screen Size 27" Panel Technology IPS

Back Light Type Edge Aspect Ratio 16:9

Native Resolution 1920x1080 (FHD) Refresh Rate 60Hz

Brightness 300nit Contrast Ratio 1,000:1

Color gamut NTSC 72% Viewing Angle(H x V) 178 X 178

Color Depth 8bit, 16.7 Million colors Response Time 9ms (G to G)

Surface Treatment(Haze) Anti glare, 3H(Haze 25%) Life time 31,000 Hrs (min)

Operation Hours (Hours/Day) 16/7 Portrait / Landscape Yes / Yes

CONNECTIVITY(JACK INTERFACE)

Input HDMI (2, HDCP1.4), RS232C IN, RJ45(LAN), IR IN, USB2.0 Type A Output Audio Out, Touch USB (USB2.0 Type B)

MECHANICAL SPECIFICATION

Bezel Color Silver Bezel Width 7.7/7.7/7.7/9.7mm

Weight(Head) 4.2Kg Packed Weight 6.2Kg

Monitor Dimension(W x H x D) 614.9 x 355.3 x 15.1mm Carton Dimensions(W x H x D) (Box outer size) 707 x 171 x 451mm

VESA™ Standard Mount Interface 200x100

KEY FEATURE(HARDWARE)

Internal Memory 8GB(System 5GB + Available 2.48GB) Temperature Sensor Yes

Acceleration(Gyro) Sensor Yes

KEY FEATURE(SOFTWARE)

webOS ver. webOS 6.0 Embedded CMS Local Contents Scheduling, Group Manager

USB Plug & Play Yes Fail over Yes

Background Image Booting Logo Image, No Signal Image Video Tag Yes

Play via URL Yes Gapless Playback Yes

Setting Data Cloning Yes SNMP Yes

ISM Method Yes Status Mailing Yes

Control Manager Yes
3rd Party Compatibility Crestron Inside
Power Smart Energy Saving, PM mode, Wake on LAN, Network Ready
HDMI-CEC Yes
SI Server Setting Yes
webRTC Yes
Pro:Idiom Yes

ENVIRONMENT CONDITIONS

Operation Temperature 0 °C to 40 °C
Operation Humidity 10% to 80%

POWER

Power Supply AC 100-240V~, 50/60Hz
Power Type Built-In Power

POWER CONSUMPTION

DPM 0.5W
Power off 0.5W

CERTIFICATION

Safety CB / NRTL
EMC FCC Class "A" / CE / KC

ErP Yes

SOFTWARE COMPATIBILITY

SuperSign CMS Yes
SuperSign Control / Control+ Yes

Signage 365 Care Yes

LANGUAGE

OSD English, French, German, Spanish, Italian, Korean, Chinese(Simplified), Chinese(Original), Portugues(Brazil), Swedish, Finnish, Norwegian, Danish, Russian, Japanese, Portugues(Europe), Dutch, Czech, Greek, Arabic, Turkish, Polski

ACCESSORY

Basic Power Cord 1.55 M*1, USB Cable (Type A-Type B) 1.8 M*1, User Manual, QSG, Remote Controller(include battery 2ea), RS232C Gender, IR Receiver

SPECIAL FEATURE

Touch - Available object size for touch $\varnothing 6$ mm
Touch - Reponse Time(PC Win10 Paintbrush) 90ms

Touch - Accuracy $3.5\text{mm} \pm 0.5\text{mm}$
Touch - Interface USB2.0

Touch - Operating System Support Win 10
Touch - Multi touch point Max 10 Points