

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



Nazwa **Monitor LG 65UH7F-H**

Cena **0,00 zł**

Producent **LG**

OPIS PRODUKTU

PANEL

Screen Size 65" Panel Technology IPS

Native Resolution 3840 x 2160 (UHD) Brightness 700nit (Typ.)

Contrast Ratio 1,100:1 Dynamic CR 500,000:1

Color gamut BT709 95% Viewing Angle (H x V) 178x178

Color Depth 10bit, 1.07 Billion colors Response Time 8ms (G to G)

Surface Treatment (Haze) 28% Operation Hours (Hours/Day) 24/7

Portrait / Landscape Yes / Yes

CONNECTIVITY

Input HDMI (2, HDCP 2.2/1.4), HDMI (1, HDCP 1.4), DP (1, HDCP 2.2/1.3), DVI-D (HDCP 1.4), Audio, USB 2.0 Type A Output DP, Audio

External Control RS232C (4 Pin Phone Jack) In / Out, RJ45 (LAN) In, IR In

MECHANICAL SPECIFICATION

Bezel Color Black Bezel Width T/R/L: 9.9mm, B: 14.4mm

Weight (Head) 28.2Kg Monitor Dimension (W x H x D) 1453.3 x 844.0 x 39.9mm

Monitor Dimensions with Stand (W x H x D) 1453.3 x 893.1 x 290.0mm Handle No

VESA™ Standard Mount Interface 300 x 300

KEY FEATURE

Key features Internal Memory 8 GB, Built-in Wi-Fi, Temperature Sensor, Auto Brightness Sensor, Acceleration (Gyro) Sensor, Local Key Operation, webOS 4.1, Embedded CMS (Local Contents Scheduling, Group Manager), USB Plug & Play, Fail Over, Background Image (Bootling Logo Image, No Signal Image), Sync Mode (RS232C Sync, Local Network Sync), Multi-screen (PIP, PBP (4)), Screen Share, Video Tag (4), Play via URL, Rotation (Screen Rotation, External Input Rotation), Gapless Playback, Tile Mode Setting (Max. 15 x 15), Setting Data Cloning, SNMP, ISM Method, Auto Set ID, Status Mailing, Control Manager, Crestron Connected@2, Smart Energy Saving, PM Mode, Wake on LAN, Beacon, HDMI-CEC3, SI Server Setting, webRTC, Pro:Idiom

ENVIRONMENT CONDITIONS

Operation Temperature 0 °C to 40 °C Operation Humidity 10 % to 80 %

POWER

Power Supply AC 100-240V~, 50/60HzPower Type Built-In Power

POWER CONSUMPTION

Typ. 130W(TBD)Max. 180W(TBD)

BTU (British Thermal Unit) 0 BTU/Hr(Typ.), 0 BTU/Hr(Max)

SOUND

Speaker Yes

CERTIFICATION

Safety CB / NRTL EMC FCC Class "A" / CE / KC

ErP / Energy Star Yes / Energy Star 8.0

OPS COMPATIBILITY

OPS Type Compatible YesOPS Power Built In No

SOFTWARE COMPATIBILITY

SuperSign CMS YesSuperSign Control / Control+ Yes / Yes

SuperSign WB YesSuperSign Media Editor Yes

LG ConnectedCare Yes

ACCESSORY

Basic Remote Controller, Power Cord, QSG, HDMI Cable, Regulation Book, Phone to RS232C

GenderOptional Stand(ST-653T), Wall bracket(LSW350B), VESA Adapter(AM-B330S), OPS Kit(KT-OPSF)

SPECIAL FEATURE

Tilt(Facedown) Yes (Max 30° degree)

*In conditions within 30°C temperature, 50% humidityIP Rating IP5x