
Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



Nazwa **Monitor LG SM3C Series 49LS75C-B**

Cena **8 490,00 zł**

Producent **LG**

OPIS PRODUKTU

PANEL

Screen Size

48.50 inches (1232.00mm) diagonal

Panel Technology

IPS

Aspect Ratio

16 : 9

Native Resolution

1,920 x 1,080 (FHD)

Brightness

700cd/m2

Contrast Ratio

1,300:1

Viewing Angle (HxV)

178 x 178

Response Time

8ms (G to G BW) typ.

Surface Treatment

Hard Coating (3H), Anti-Glare Treatment of the Front Polarizer (Haze 10%)

Life time (Typ.)

50,000 Hrs min.

Operation Hours

24 Hrs / 7 Days

Orientation

Portrait & Landscape

CONNECTIVITY

Input

HDMI (2), DP, DVI-D, Audio in, OPS

External Control

RS232C in/out, RJ45, IR / Light sensor, Pixel sensor, USB 3.0

Output

DP, External Speaker out

PHYSICAL SPECIFICATION

Bezel Color

Black

Bezel Width

7.4 mm (T/L/R/B even)

Monitor Dimension (W x H x D)

1,095 x 637 x 32 mm

Weight (Head)

15.6 kg

Monitor with Optional Stand Dimensions (W x H x D)

1,095 x 700 x 298 mm

Weight (Head + Stand)

17.0 kg

Carton Dimensions (W x H x D)

1,197 x 760 x 134 mm

Packed Weight

18.7 kg

VESA TM Standard Mount Interface

400 x 400 mm

SPECIAL FEATURES

Yes

Temperature sensor, Auto brightness sensor, Tile Mode, DPM select, DPM wake up, Energy saving, Smart energy saving, File play with USB, PIP/PBP(2), Internal memory 16GB (System 4GB + Available 12GB), Wi-Fi dongle ready (802.11n), USB cloning, Fail over

ENVIRONMENTAL CONDITIONS

Operating Temperature

0°C to 40°C

Operating Humidity

10% to 80%

POWER

Power Supply

100-240V~, 50/60Hz

Power Type

Built-in Power

Power Consumption-Typ

125 W (TBD)

Power Consumption Smart Energy Saving

90 W (TBD)

STANDARD (CERTIFICATION)

Safety

UL / cUL / CB / TUV / KC

EMC

FCC Class "A" / CE / KCC

ErP / Energy Star

NA / Yes (Energy Star 7.0)

MEDIA PLAYER COMPATIBILITY

OPS Type Compatible

Yes

External Media player Attachable

Yes (MP500/MP700)

SOFTWARE COMPATIBILITY

SuperSign W/Lite

Yes

SuperSign C

Yes

ACCESSORIES

Basic

Remote controller (2ea batteries included), Power cord, IR/Light sensor receiver, QSG, Regular book (depend on regional standard), HDMI cable

Optional

SP-2100 (External speaker), ST-200T, AN-WF500 (Wi-Fi USB dongle), KT-OPSA (OPS kits), KT-SP0 (Pixel sensor)

UPC

49LS75C-B

7 19192 60628 9