

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



Nazwa **Monitor LG stretched-display 88BH7D**

Cena **48 641,00 zł**

Producent **LG**

OPIS PRODUKTU

PANEL

Screen Size

88" (87.80" diagonal)

Panel Technology

IPS

Aspect Ratio

32:9

Native Resolution

3,840 x 1,080 (UHD)

Brightness

700 cd/m2 (Typ)

Contrast Ratio

1,100:1 (Typ)

Dynamic CR

500,000:1 (Typ)

Viewing Angle (HxV)

178 x 178

Color Depth

10bit(D), 1.07 Billion

Response Time

8ms (G to G BW) typ.

Surface Treatment

AGLR (Haze 3%)

Orientation

Landscape & Portrait Mode

CONNECTIVITY

Input

HDMI (3), DP, OPS, DVI-D, Analog Audio, USB 2.0, USB 3.0, SD Card

Output

DP, Analog Audio

External Control

RS232C In/Out, RJ45 In/Out, IR & Light Sensor, Pixel Sensor

PHYSICAL SPECIFICATION

Bezel Color

Black

Bezel Width

4.4 mm (L/R), 5.9 mm (U/D)

Monitor Dimension (W x H x D)

85" x 26" x 4.1"

Weight (Head)

75.4 lbs

Carton Dimensions (W x H x D)

89.5" x 28.2" x 8.3"

Packed Weight

112.9 lbs (Pallet included)

Handle

Yes

VESA™ Standard Mount Interface

600 mm x 400 mm

SPECIAL FEATURES

Yes

Temperature Sensor, Auto Brightness Sensor, Tile Mode, Natural Mode@Tile Mode, ISM Method, DPM Select, Energy Saving, Smart Energy Saving, File Play with USB/SD/Internal Memory, 2/3/4PBP, Internal Memory 8GB (System 4GB + Available 4GB), Wi-Fi Dongle Ready(Support Beacon function), 4K Up

Scaling

ENVIRONMENT CONDITIONS

Operation Temperature Range

32 °F to 104 °F

Operation Humidity Range

10% to 80%

POWER

Power Supply

100-240 V~, 50/60 Hz

Power Type

Built-in Power

Power Consumption Typ. / Max.

400 W / 500 W

Power Consumption Smart Energy Saving

30% of typical

STANDARD (CERTIFICATION)

Safety

UL / cUL / CB / TUV / KC

EMC

FCC Class "A" / CE / KC

ErP / Energy Star

Yes / No

MEDIA PLAYER COMPATIBILITY

OPS PC compatible (optional)

Yes

External Media player Attachable

No

SOFTWARE COMPATIBILITY

Content Management Software

SuperSign Premium

Control and Monitoring Software

SuperSign C
ACCESSORIES

Basic

Remote Controller (including battery 2ea), Power Cord, DP (2.6M), RS-232C Cable (3M), Owner's Manual (Website upload)

Optional

AN-WF500 (Wi-Fi USB Dongle), MP700, KT-OPSA (OPS KIT), KT-SP0 (RGB Sensor) ** Stand is not available

OTHER

UPC

7 19192 61563 2

Warranty

Warranty: 3-Year Limited Warranty (Parts and Labor)