

---

## Inteligentna Elektronika

Ul. Raduńska 36A  
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl

---



Nazwa	<b>Monitor OLED LG Flexible Curved Open Frame 55EF5F-P</b>
-------	--

Cena	<b>41 000,00 zł</b>
------	---------------------

Producent	<b>LG</b>
-----------	-----------

---

## OPIS PRODUKTU

### Panel

Screen Size: 55"

Panel Technology: OLED

Native Resolution: 1,920 x 1,080 (FHD)

Brightness: 150 / 400 nit (APL 100% / 25%)

Contrast Ratio: x150,000 : 1

Dynamic CR: No

Color gamut: BT709 120 %

Viewing Angle (H x V): 178 x 178

Color Depth: 1.07 Billion Colors (10bit)

Response Time: 1 ms (G to G)

Surface Treatment (Haze): No

Operation Hours (Hours / Day): 18 / 7 (Moving Content Only)

Orientation: Landscape & Portrait

### Connectivity

Input: HDMI (HDCP 2.2), DP (HDCP 1.3), USB 2.0 Type A (2)

Output: DP, Audio

External Control: RS232C In / Out, RJ45 In / Out, IR In (External IR Receiver)

### Mechanical Specification

Bezel Color

Black

Bezel Width (T / R / L / B)

0.6 / 6.7 / 6.7 / 0.6 mm (Off Bezel)

5.0 / 13.2 / 7.8 / 5.0 mm (Off Bezel)

Weight (Head)

7.8 kg

(Signage Box) 3.5 kg

Monitor Dimension (W × H × D)

701.4 x 1,219.7 x 38.0 mm (Head, w/Pemnut)

701.4 x 1,219.7 x 12.4 mm (Head, w/o Pemnut)

(Signage Box) 413 x 353 x 57.3 mm

Monitor Dimensions with Stand (W × H × D)

No

VESA™ Standard Mount Interface

No

Feature

Special Features: Internal Memory (64GB), Temperature Sensor, FAN, webOS 4.0, Embedded CMS (Local Contents Scheduling, Group Manager), USB Plug & Play, Fail Over, Sync Mode (RS-232C Sync, Local Network Sync), Video Tag (4), Rotation (Screen Rotation, External Input Rotation), Gapless Playback, Tile Mode Setting, Setting Data Cloning, SNMP, ISM Method, Auto Set ID, Status Mailing, Control Manager, Crestron Connected®(Network based control ), PM Mode, Wake on LAN, HDMI-CEC( Compatibility may differ by equipment.), SI Server Setting, webRTC, Pro:Idiom

Environment Conditions

Operation Temperature: Operation Humidity

0°C to 40°C: 10 % to 80 %

Power

Power Supply: Power Type

AC 100 - 240 V ~, 50 / 60 Hz: Built-In Power

Power Consumption

Typ./Max: BTU (British Thermal Unit)

309 W / 318 W (Based on 8 color bar): 1,054 BTU/Hr (Typ.), 1,085 BTU/Hr (Max.)

Sound

Speaker: No

Certification

Safety: CB / NRTL

EMC: FCC Class "A" / CE / KC

ErP: Yes (EU Only)

Media Player Compatibility

OPS type compatible: OPS Power Built In

No: No

Software Compatibility

SuperSign CMS: Yes

SuperSign Control / Control+: Yes

SuperSign WB: Yes

SuperSign Media Editor: Yes

Signage365Care: Yes (The availability can differ by region.)

Accessory

Basic: Remote Controller, Power Cord, QSG, IR Receiver, Regulation Book, Phone to RS232C Gender, FFC Cables (220 mm × 4 ea for Connection Between Panel and Signage Box), DP Cable (2 M), RS232 Cable (4p-4p, 1.5 M), LC Cable (VLC, 3 M), Tape (4 ea for Cabling), Screw (M3 × L4.5, 30 ea / M3 × L5.5, 50 ea), Shield Cover Ass'y, Tiling Set Fixer 6 ea, Flex Bar 2 ea