

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



Nazwa

**Monitor Mitsubishi 55" Flat LCD Display
Wall VS-L55HM70U**

Cena

0,00 zł

Producent

Mitsubishi

OPIS PRODUKTU

Specification Overview

Model Name

VS-L55HM70U

Display Type

TFT-LCD (SPVA Mode)

Viewable Area

55" (139.7 cm) diagonal

Native Resolution

1920 x 1080 pixels

Brightness

700cd/m²(Typ.)@Bright Mode

500cd/m²(Typ.)@Normal Mode

350cd/m²(Typ.)@Eco Mode

Colour Depth

16.7 million colours

Contrast Ratio

3500:1 (typical)

Viewing Angle (Left/Right, Up/Down)

±89°, ±89° (typical)

Mullion (Total)

5.7 mm

Back Light Operating Life

50,000 hours

Optional Input Board Slot

x 3 (One VC-B70DC card is pre-installed)

Control Signal Input

RS-232C: DSub 9-pin

LAN: RJ45(10BASE-T / 100BASE-TX)

DSub 9-pin x 2(IN/OUT) Mitsubishi Original Control Link

Wired Remote: F3.5 Jack

IR Receiver (optional)

Overlay Function

Max. 6 Windows per each screen (with VC-B70V2)

Max. 3 Windows per each screen (with other boards)

Control S/W(Optional)

Mitsubishi D-Wall Software Suite

Power Consumption

210W(Typ.)@Bright Mode

170W(Typ.)@Normal Mode

150W(Typ.)@Eco Mode

Voltage Range

100 VAC to 240 VAC \pm 10%, 50/60 Hz \pm 1 Hz

Dimensions (W x H x D)

1215.3mm x 686.1mm x 173mm

Operating Condition

5°C ~ 35°C; 20% - 80% Humidity in Normal/Eco Mode

5°C ~ 30°C; 20% - 80% Humidity in Bright Mode

Weight

40kg

*Specifications are subject to change without notice