

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



Nazwa **Monitor Mitsubishi 55" LED display
LM55P2**

Cena **0,00 zł**

Producent **Mitsubishi**

OPIS PRODUKTU

LM55P2 (NEW)

Screen size
55 "

Resolution
Full HD 1920x1080 pixels

LCD type
TFT LCD (SPVA Mode)

Brightness
700cd/m² @High Bright Mode, 500cd/m² @Standard Mode

Contrast ratio
3500 :1

Back light technology
LED (Direct)

Viewing angle (H/V)
178°

Display orientation
Landscape / Portrait

Functions

DVI-D Daisy chain function (Up to 4 units) DisplayPort1.2a Daisy chain function (Up to 4 units) * apply to 4K image Scaling function (Up to 5x5), Dynamic brightness balance function, Picture-in-Picture 2-screen layering

Video signal terminal

Input: DVI-D (with HDCP) x 1, HDMI x 1, DisplayPort (1.2a) x 1, D-sub15 x 1, YPbPr (BNC x 3) x 1, Comp.Video(BNC Y:shared with YPbPr) x1 Output: DisplayPort (1.2a), DVI-D (with HDCP) x 1

Control signal terminal

RS-232C, D-Sub 9 pins (input, output), Wire remote: F3.5Jack (input, output), IR Receiver (input, output), LAN: RJ45 x 1 (10Base-T/100Base-TX)

Power consumption

2.1W Stand-by state, 170W@Standard Mode / 200W@High Bright Mode

Thermal dissipation

580 BTU/h@Standard Mode / 683 BTU/h@High Bright Mode

Operating current

2.4 / 1.2 Amp Amp

Optional Accessories

Remote Control kit DP-01RK / SDI input board DP-1SDI-3G / Long-distance transmission VC-LM1HD / Wall mount bracket BR-LM1KK

Optional Slot

Intel OPS slot x 1