

## Inteligentna Elektronika

Ul. Raduńska 36A  
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



**NEC**  
NEC Technologies

Nazwa **Monitor NEC V323-2-AVT**

Cena **0,00 zł**

Producent **Nec**

## OPIS PRODUKTU

Dane techniczne:

Display

Panel Technology S-IPS Aspect Ratio 16:9

Native Resolution 1920 x 1080 Backlight Type LED Edge-lit

Brightness (maximum) 450cd/m2 Contrast Ratio (typical) 1300:1

Viewing Angle (typical) 178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR>10 Refresh Rate 60Hz

Active Screen Area 27.5x 15.5in. / 698.4 x 392.9mm Orientation Landscape/Portrait

Displayable Colors More than 16.7 million

Synchronization Range

Horizontal (Analog/Digital) Analog: 15.625 / 15.734 / 31.5 - 91.1 KHz, Digital: 31.5 - 91.1KHz

Input Signal

Video Analog RGB 0.7 Vp-p/75 Ohms , Digital TMDS / DisplayPort Sync Analog: Separate sync: TTL Level (Positive/Negative)

, Sync on green: (0.3Vp-p negative), Digital: TMDS / DisplayPort

Signal Compatibility/Connectivity

PC Signal Compatibility Yes Macintosh Signal Compatibility Yes

Video Analog RGB 0.7 Vp-p/75 Ohms , Digital TMDS / DisplayPort Sync Analog: Separate sync: TTL Level (Positive/Negative)

, Sync on green: (0.3Vp-p negative), Digital: TMDS / DisplayPort

Input Terminals

Digital:

DisplayPort, HDMI, DVI-D

Audio:

Stereo Mini-Jack, HDMI Audio, DisplayPort Audio

External Control:

RS-232C, Ethernet (RJ45)

Output Terminals

Digital:

DVI-D

Audio:

Stereo Mini-Jack

External Control:

RS-232C

Power Consumption (typical)

On 48W ECO Mode Standby <1W

Physical Specifications

Bezel Width (Left/Right, Top/Bottom) 0.9 in. / 0.9 in., 0.9 in. / 0.9 in. ; 24.0mm/24.0mm, 24.0mm/24.0mm

Dimensions (WxHxD)

Net (with stand):

29.5 x 19.6 x 9.4 in. / 750.0 x 497.1 x 240.0mm

Net (without stand):

29.5 x 17.5 x 2.4 in. / 750.0 x 444.5 x 60.8mm

Shipping:

34.5 x 22.9 x 6.8 in. / 876.0 x 582.0 x 172.0mm

Shipping:

25.0lbs / 11.4kg

Weight

Net Weight (with stand):

23.8lbs. / 10.8kg

Net Weight (without stand):

20.9lbs / 9.5kg

VESA Hole Configuration Specifications

200 x 200mm (4-hole)

Environmental Conditions

Operating Temperature 41-104°F / 5-40°C Operating Humidity 20-80%

Operating Altitude 9843 ft. / 3000m Storage Temperature -4-140°F / -20-60°C

Storage Humidity 10-90% Storage Altitude 40,000 ft. / 12,192m

Limited Warranty (parts & labor)

3 years

Additional Features

Advanced thermal capabilities

Advanced cooling system

TileMatrix (10x10)

TileComp

Separate group/Monitor ID function

Ethernet Control and Communication

RS-232 Control and Communication

Carbon footprint meter

Plug and Play (DDC/CI, DDC2B)

Scheduler (w/ real-time clock)

Screen saver function

POP

Side-by-Side

Touch- and protective screen-ready

Variable picture modes

Input labeling

Backlight adjust  
Aspect ratio control  
Built-in speaker  
Integrated SB-03TM Digital Tuner

Accessories

Optional

ST-322 (Stand)

Wall Mount (WMK-3257)

Contrast Ratio

1300:1