

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



NEC
NEC Technologies



Nazwa **Monitor NEC V652-THS**

Cena **0,00 zł**

Producent **Nec**

OPIS PRODUKTU

Display

Panel Technology UV²A Aspect Ratio 16:9

Native Resolution 1920 x 1080 Backlight Type LED Edge-lit

Brightness (maximum) 450cd/m² Contrast Ratio (typical) 4000:1

Viewing Angle (typical) 178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR>10 Refresh Rate 60Hz

Active Screen Area 56.2 x 31.6 in. / 1428.5 x 803.5mm Orientation Landscape/Portrait

Displayable Colors More than 16.7 million

Synchronization Range

Horizontal (Analog/Digital) 31.5-91.1 kHz

Input Signal

Video Analog RGB 0.7 Vp-p/75 Ohms Sync Separate sync: TTL Level (Positive/Negative)

Composite sync: TTL Level (Positive/Negative)

Composite sync on green: (0.3Vp-p negative 0.7Vp-p positive)

Signal Compatibility/Connectivity

PC Signal Compatibility Yes Macintosh Signal Compatibility Yes

Video Analog RGB 0.7 Vp-p/75 Ohms Sync Separate sync: TTL Level (Positive/Negative)

Composite sync: TTL Level (Positive/Negative)

Composite sync on green: (0.3Vp-p negative 0.7Vp-p positive)

Input Terminals

Digital:

DisplayPort, HDMI, DVI-D

Audio:

Stereo Mini-Jack, HDMI Audio, DisplayPort Audio

External Control:

RS-232C, Ethernet (RJ45), IR Remote, DDC/CI

Output Terminals

Digital:

DVI-D

Audio:

RCA Audio, External Speaker Jack (2)

External Control:

RS-232C

Power Consumption (typical)

On 185W ECO Mode Standby <2W

Physical Specifications

Bezel Width (Left/Right, Top/Bottom) 2.1 in./2.1 in., 2.0 in./2.1 in. ; 53.5mm/53.5mm, 50.5mm/50.5mm

Dimensions (WxHxD)

Net (with stand):

60.6 x 37.2 x 20.2 in. / 1540.4 x 944.7 x 512mm

Net (without stand):

60.6 x 35.8 x 3.5 in. / 1540.4 x 909.2 x 88.3mm

Shipping:

71.5 x 46.9 x 14.8 in. / 1816 x 1192 x 375mm

Shipping:

165.35 lbs. / 75 kg

Weight

Net Weight (without stand):

156.53 lbs. / 71 kg

VESA Hole Configuration Specifications

400 x 400mm (4-hole)

Environmental Conditions

Operating Temperature 41-104°F / 5-40°C Operating Humidity 20-80%

Operating Altitude 9843 ft. / 3000m Storage Temperature -4-140°F / -20-60°C

Storage Humidity 10-90% Storage Altitude 40,000 ft. / 12,192m

Limited Warranty (parts & labor)

3 Years Onsite Service for displays and 3 YR Standard Mac OS Appliance in these bundles

Additional Features

Integrated Temperature Sensors

Thermodynamic Cooling Fans

Ethernet control and communication

RS-232Control and communication

AMX Beacon Compatible, Crestron Connected Compatible

Full 24/7 Scheduler

OPS expansion slot

Custom Input Detect Options

Auto Power On Integrated 10W Speakers Full Steel Chassis Plug and Play DDC2B Full Scheduler Function

Accessories

Optional

External Speakers (SP-TF1 or SP-RM1)

TH-CAM

TH-CART

TH-WM

Contrast Ratio

4000:1

