
Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



Nazwa	Projektor Optoma W345
-------	------------------------------

Cena	2 174,00 zł
------	--------------------

Producent	Optoma
-----------	---------------

OPIS PRODUKTU

W345 Specification

Display Technology

Single 0.65" WXGA DC3 DMD chip DLP® Technology by Texas Instruments

Native Resolution

WXGA 1280 x 800

Brightness¹ (Bright Mode)

3300 ANSI Lumens

Contrast

22,000:1

Lamp Life² Eco+/Dynamic/Eco/Bright/Education cycle

8000/7000/6000/5000/10000 (hrs)

Throw Ratio ³

1.19 – 1.54:1

Zoom Type

1.3x Manual

I/O Connectors

HDMI (1.4a 3D support), VGA (YPbPr/RGB), Composite, Audio In 3.5mm, VGA out, Audio Out 3.5mm, RS232, USB-A Power (1A)

Speaker

2

Keystone Correction

± 40° Vertical

Weight (kg)

2.41

Dimensions (W x D x H) (mm)

298 x 230 x 96.5

Aspect Ratio

16:10 Native, 16:9/4:3 Compatible

Offset

115%

Projection Screen Size

0.92 – 7.65m (36.1" to 301.1") Diagonal 16:10

Projection Distance

1.2 - 7.7m

Projection Lens

F/2.5~2.78; f=16.91~21.6mm

Uniformity

75%

Computer Compatibility

FHD, HD, WXGA, UXGA, SXGA, XGA, SVGA, VGA, Mac

Video Compatibility

PAL (B, D, G, H, I, M, N, 4.43MHz), NTSC (M, J, 3.58MHz, 4.443MHz), SECAM (B, D, G, K, K1, L, 4.25MHz, 4.4MHz, 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz) 1080p(24/50/60Hz)

3D Support

Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification.

3D Compatibility

Side-by-Side: 1080i50 / 60, 720p50 / 60

Frame-pack: 1080p24, 720p50 / 60

Over-Under: 1080p24, 720p50 / 60

Horizontal Scan Rate

15.3 - 91.1kHz

Vertical Scan Rate

24 - 85Hz (120Hz for 3D)

Displayable Colours

1073.4 Million

Noise Level (Eco mode)

29dB

Power Supply

100-240V, 50-60Hz

Power Consumption

225W Bright mode / 187W Eco mode (< 0.5W Standby)

Lamp Type

195W

Operating Conditions

5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m

Security

Security bar, Kensington lock, password protection

On Screen Display

26 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Vietnamese, Romanian, Indonesian

Standard Accessories

AC power cord, VGA cable, remote control, battery, quick start card, CD user manual

Optional Accessories

DLP® Link™ 3D glasses, wireless, ceiling mount

Optional Wireless

Yes

RoHS

Compliant

1Lamp based projectors brightness and lifetime will vary depending on selected projector mode, environmental conditions and usage. As is common with all lamp based projectors, brightness will

decrease over the lamp lifetime. LED projectors do not have a replaceable lamp and the brightness does not decay significantly over the product lifetime.

2Typical lamp life achieved through testing. Will vary according to operational use and environmental conditions

3 +/- 5% tolerance