

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



Nazwa **Projektor Optoma W402**

Cena **2 874,00 zł**

Producent **Optoma**

OPIS PRODUKTU

W402 Specification

Display Technology

Single 0.65" WXGA DC3 DMD chip DLP® Technology by Texas Instruments

Native Resolution

WXGA 1280 x 800

Brightness1 (Bright Mode)

4500 ANSI Lumens

Contrast

20,000:1

Noise Level (Eco mode)

31dB

Weight (kg)

2.57

I/O Connectors

HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB), S-Video, Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out, RS232, USB mouse/service, RJ45

Computer Compatibility

UXGA, SXGA, XGA, SVGA, VGA, Mac

Video Compatibility

PAL (B, D, G, H, I, M, N, 4.43MHz), NTSC (M, J, 3.58MHz, 4.443MHz), SECAM (B, D, G, K, K1, L, 4.25MHz, 4.4MHz, 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz) 1080p(24/50/60Hz)

Displayable Colours

1073.4 Million

Projection Lens

F/2.5~2.67; f=21.8~23.98mm, 1.2x Manual Zoom

Throw Ratio

1.28 - 1.536:1

Projection Screen Size

0.93 - 7.65m (27.2" to 300") Diagonal 16:10

Projection Distance

1.2 - 12m

Zoom Type

1.2x Manual

Aspect Ratio

16:10 Native, 16:9/4:3 Compatible

Offset

112.4%

Horizontal Scan Rate

15.3 - 91.1kHz

Vertical Scan Rate

24 - 85Hz

Lamp Type

260W

Lamp Life² Bright

3000 (hrs)

Keystone Correction

± 40° Vertical

Dimensions (W x D x H) (mm)

315 x 224 x 102

Power Supply

100-240V, 50-60Hz

Power Consumption

306W Bright mode / 257W Eco mode (< 0.5W Standby)

Operating Conditions

5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m

Uniformity

80%

Security

Security bar, Kensington lock, password protection

Standard Accessories

Carry bag, AC power cord, VGA cable, remote control, battery, quick start card, CD user manual

Optional Accessories

DLP® Link™ 3D glasses, wireless, ceiling mount

RoHS

Compliant

3D Support

Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification.

3D Compatibility

Side-by-Side: 1080i50 / 60, 720p50 / 60

Frame-pack: 1080p24, 720p50 / 60

Over-Under: 1080p24, 720p50 / 60

Speaker (Watts)

10

On Screen Display

19 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish, Greek, Norwegian/Danish, Hungarian, Czech, Turkish, Romanian, Farsi and Arabic.

Optional Wireless

Yes

1Lamp based projectors brightness and lifetime will vary depending on selected projector mode, environmental conditions and usage. As is common with all lamp based projectors, brightness will

decrease over the lamp lifetime. LED projectors do not have a replaceable lamp and the brightness does not decay significantly over the product lifetime.

2Typical lamp life achieved through testing. Will vary according to operational use and environmental conditions