

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



Nazwa	Projektor Optoma W490
-------	------------------------------

Cena	0,00 zł
------	----------------

Producent	Optoma
-----------	---------------

OPIS PRODUKTU

Display Technology□Single 0.65" WXGA chip, DLP® Technology from Texas Instruments™

Resolution□WXGA 1280 x 800

Brightness□5000 ANSI Lumens

Contrast Ratio□10,000:1 (full on/full off)

Lamp Life2 Eco/Bright□3500/3000 (hrs)

Throw Ratio 3□1.48:1~2.35:1

Zoom Type□Digital Zoom: 0.8 ~ 2.0; Optical Zoom: 1.6x Manual zoom

Lens Shift□Vertical: +16% (constraints apply see user manual for details)

I/O Connectors□3x HDMI 1.4a (2 with MHL, 2 rear and 1 on top), 1x VGA-In, 1x VGA-Out, 1x Composite Video (RCA-Y), 2x Audio-In (3.5mm jack), 1x Audio-Out (3.5mm jack), 1x RS-232C (9pin d-sub), 1x mini-USB (service/control), 1x USB-A (5V/1.5A out), RJ45 (LAN), 1x 3D vesa port, AC power (3 pin)

Speaker (Watts)□Two 16-Watt Speaker

Keystone Correction□±30° Vertical; ±30° Horizontal

Weight□10.2 lb (4.6 kg)

Dimensions (W x D x H)□14.5" x 5.2" x 12" (369 x 132 x 295 mm)

Aspect Ratio□16:10 (Native), 4:3, 16:9, Auto

Offset□96%~112%

Projection Screen Size□25.6"~301.1" (0.65~7.64 m), Diagonal 16:10

Projection Distance□51.18"~377" (1.3~9.6 m)

Projection Lens□F=2.5~3.26, f=20.91~32.63 mm; manual focus

Uniformity□70%

Maximum Resolution□1080p (1920 x 1080)

Computer Compatibility□UXGA, SXGA, XGA, SVGA, VGA, WXGA, 1080p, Mac

Video Compatibility□PAL (B, D, G, H, I, M, N, 4.43MHz), NTSC (M, J, 3.58MHz, 4.443MHz), SECAM (B, D, G, K, K1, L, 4.25,MHz, 4.4MHz, 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz) 1080p(24/50/60Hz)

3D Compatibility□Side-by-Side:1080i(50/60Hz)

Frame-pack: 1080p(24Hz), 720p(50/60Hz)

Over-Under: 1080p(24Hz), 1080i(50/60Hz), 720p(50/60Hz)

3D glasses are needed and are sold separately.

Refer to user manual for details.

Horizontal Scan Rate□15.375–91.146 KHz

Vertical Scan Rate□24–85 Hz (120 Hz for 3D feature projector)

Displayable Colors□1.07 Billion

Noise Level (Eco mode)□29dB

Power Supply□AC input 100–240V, 50–60 Hz, auto-switching

Power Consumption□421W Max (Bright), 329W Max (ECO), <0.5W (Standby)

Lamp Type□310-Watt

Operating Conditions□41–113°F (5–45°C), 85% max humidity

Security□Kensington® lock port, security bar, and keypad lock

Remote Control□IR remote

Standard Accessories□W490 projector, AC power cord, VGA cable, remote control, batteries, multilingual CD-ROM user's manual, basic user manual and warranty card

Optional Accessories□Universal ceiling mount, Optoma screen, DLP® Link™ 3D glasses, wireless HDMI system

Optional Wireless□Yes

Projection method□Front, rear, ceiling mount, table top

Warranty□3-Year Optoma Express Service, 1-Year on Lamp

1Lamp based projectors brightness and lifetime will vary depending on selected projector mode, environmental conditions and usage. As is common with all lamp based projectors, brightness will decrease over the lamp lifetime. LED projectors do not have a replaceable lamp and the brightness does not decay significantly over the product lifetime.

2Typical lamp life achieved through testing. Will vary according to operational use and environmental conditions

3 +/- 5% tolerance