

---

## Inteligentna Elektronika

Ul. Raduńska 36A  
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: [info@centrumprojekcji.pl](mailto:info@centrumprojekcji.pl)

---



Nazwa	<b>Projektor Optoma X320UST</b>
Cena	<b>4 998,00 zł</b>
Producent	<b>Optoma</b>

---

## OPIS PRODUKTU

### Display Technology

Single 0.55" XGA DC3 DMD chip DLP® Technology by Texas Instruments

### Native Resolution

XGA 1024 x 768

### Brightness1 (Bright Mode)

4000 ANSI Lumens

### Contrast

20,000:1

### Noise Level (Eco mode)

28dB

### Weight (kg)

4.78

### I/O Connectors

2 x HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB), Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out (Shared with VGA2), RJ45, RS232, USB remote mouse/service, 12V trigger, Mic In, 3D-Sync, USB-A Power

### Computer Compatibility

UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac

### Video Compatibility

PAL (B, D, G, H, I, M, N, 576i/p), NTSC (M, 4.43/3.58 MHz, 480i/p), SECAM (B, D, G, K, K1, L) HD (1080i, 720p)

### Displayable Colours

1.07 Billion

### Projection Lens

F/2.4; f=3.72mm, Fixed Zoom

Throw Ratio 3

0.33:1

Projection Screen Size

1.78 – 2.54m (70" – 100") Diagonal 4:3

Projection Distance

0.47 - 0.68m

Zoom Type

Fixed

Aspect Ratio

4:3 Native, 16:9 Compatible

Offset

117%

Horizontal Scan Rate

15.3 - 91.1kHz

Vertical Scan Rate

24 - 85Hz (120Hz for 3D)

Lamp Type

260W

Lamp Life2 Eco+/Dynamic/Eco/Bright

6500/5000/5000/3000 (hrs)

Keystone Correction

± 20° Vertical

Dimensions (W x D x H) (mm)

385 x 310 x 99

Power Supply

100-240V, 50-60Hz

Power Consumption

310W Bright mode / 260W Eco mode (< 0.5W Standby)

Operating Conditions

5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m

Uniformity

85%

Security

Security bar, Kensington lock, password protection

Standard Accessories

AC power cord, VGA cable, remote control, battery, quick start card, CD user manual

Optional Accessories

DLP® Link™ 3D glasses, wireless, wall mount

RoHS

Compliant

3D Support

Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK),

Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification.

3D Compatibility

Side-by-Side: 1080i50 / 60, 720p50 / 60

Frame-pack: 1080p24, 720p50 / 60

Over-Under: 1080p24, 720p50 / 60

Speaker

16

On Screen Display

25 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese,

Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Romanian, Slovenian

Optional Wireless

Yes

1Lamp based projectors brightness and lifetime will vary depending on selected projector mode, environmental conditions and usage. As is common with all lamp based projectors, brightness will decrease over the lamp lifetime. LED projectors do not have a replaceable lamp and the brightness does not decay significantly over the product lifetime.

2Typical lamp life achieved through testing. Will vary according to operational use and environmental conditions

3 +/- 5% tolerance