
Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



Nazwa	Projektor Optoma ZU650
-------	-------------------------------

Cena	0,00 zł
------	----------------

Producent	Optoma
-----------	---------------

OPIS PRODUKTU

ZU650 Specification

Display Technology

DLP™ Technology by Texas Instruments, 0.67" WUXGA, DC3, Type A chip

Native Resolution

WUXGA 1920 x 1200

Brightness1 (Bright Mode)

6000 centre lens (5,500 ANSI lumens)

Contrast

2,000,000:1 ExtremeBlack enabled (2000:1 full on/off)

ANSI Contrast

250:1

Noise Level (Eco mode)

33dB

Weight (kg)

18Kg

I/O Connectors

1 x HDMI, 1 x DVI-D, HDBaseT, Component Video, 1 x VGA, VGA Out, RJ45, RS232, wired remote in, wired remote out, USB A

Maximum Resolution

Native WUXGA (1920 x 1200)

Computer Compatibility

WUXGA, HD, UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized, VESA, PC and Macintosh Compatible

Video Compatibility

PAL (625/576i/p), SECAM, NTSC (525/480i/p), HDTV (720p, 1080i/1080p)

Displayable Colours

16.7 million

Projection Lens

5 x lens options "no lens supplied as standard"

Throw Ratio 3

0.75 ~ 5.50 "lens dependent"

Projection Screen Size

Dependent upon lens

Projection Distance

Dependent upon lens

Zoom Type

Motorised

Aspect Ratio

16:10 native, 16:9/4:3 compatible

Horizontal Scan Rate

15kHz to 100kHz

Vertical Scan Rate

25Hz to 85Hz

Lamp Type

Laser Phosphor

Lamp Life² Bright

20000 (hrs)

Dimensions (W x D x H) (mm)

484 x 509 x 185mm without lens

Remote Control

Infra-red remote control, wired connection

Power Supply

100 – 240V AC @ 50 – 60Hz

Power Consumption

560W \pm 20%@ 110VAC in normal brightness mode

Uniformity

85% (centre)

Security

4-digit PIN code, Kensington lock port, security bar

Standard Accessories

VGA cable, AC power cord, Infra-red remote control, 2 x batteries, user manual CD, quick start card,

WEEE card, warranty card

RoHS

RoHS and WEEE

Lens Shift

Motorised lens shift, focus and zoom horizontal: \pm 15% (typical; tolerance \pm 4%) vertical: \pm 50% (typical; tolerance \pm 4%)

Lens Options

A15-0.75-0.95

A01-0.95-1.22

A02-1.22-1.53

A03-1.52-2.92

A13- 2.90-5.50

Conformances

CE, TUV-GS, CB

Operating Temperature

for 0 ~ 2500 ft, 5 ~ 40°C

for 2500 ~ 5000 ft, 5 ~ 35°C

for 5000 ~ 10000 ft, 5 ~ 30°C

Warranty

1 Year

360' Operation

Yes

Portrait Mode

Yes

On Screen Display

18 languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish, Greek, Norwegian/Danish, Hungarian, Czech

Optional Wireless

Yes

Features

5 x optional Lens, motorised full lens shift, Crestron RoomView®, PJ-Link, 360° operation