

## Inteligentna Elektronika

Ul. Raduńska 36A  
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



**Panasonic**  
ideas for life

Nazwa **Monitor Dotykowy Panasonic TH-86SQ1-IG**

Cena **0,00 zł**

Producent **Panasonic**

## OPIS PRODUKTU

Panel Size 86-inch (2174,2 mm)

Panel Type E-LED

Aspect Ratio 16:09

Effective Display Area (W x H) 1895 x 1065,9 mm (74.6" x 41.96")

Resolution (H x V) 3840 x 2160

Brightness (typ.) 500 cd/m<sup>2</sup>

Contrast Ratio 1100:1

Response Time 8.0 ms (Typ) (G to G)

Viewing angle [(T/B)/(L/R)] 178°/178° (CR≥10)

Panel Surface Treatment Anti-glare, anti-reflective with the level of haze approx. 5%(±3%)

Detection Method InGlass™ Touch Detection of human finger, passive stylus

Touch Operation Up to 20-point multi-touch

Power Supply 12-24V / 1A external

OS Win 7/8/10, Android, Mac OS\*4, Linux

Terminals | HDMI In HDMI Type A Connector x 4

Terminals | DisplayPort IN DisplayPort x 1

Terminals | DisplayPort OUT DisplayPort x 1

Terminals | PC In Mini D-sub 15-pin x 1

Terminals | Serial D-sub 9pin x 1, RS-232C Compatible

Terminals | IR In Stereo Mini jack (M3) x 1

Terminals | Audio In Pin Jack (L/R) x2

Terminals | Audio Out Stereo Mini jack (M3) x 1, SPDIF x 1

Terminals | USB USB Connector Type-A x 2, Type-C x 1 (Internal) Type-A x 1

Terminals | Slot x1 (Intel® SDM specification, Corresponding size SDM-S / SDM-L, 12V x max. 3.5A)

Terminals | LAN RJ45 x 1

Power Requirements 110-127 V AC, 50/60 Hz, 220-240 V AC, 50/60 Hz

Power Consumption max. 371 W (319 W)\*5

Power Off Condition 0 W

Stand-by Condition Approx. 0.5 W

Wi-Fi Dongle type

Carton Dimensions (W x H x D) 1.966,5 x 1137,5 x 72,7 [88,6]\*6 mm

Carton Size (W x H x D) (mm) 2.163 x 1.405 x 380 mm

Weight 95,9 kg

Gross Weight 118 kg

Wall-Hanging Pitch VESA Compliant 600 x 400 mm (23.6" x 15.8" ), M8

Protective Glass Thickness 3 mm

Bezel Width 33 mm

Built-in Speaker 24 W [12 W + 12 W]

Orientation Landscape / Portrait

Tilting angle\*1 Landscape setting: 0 - 20 degrees forward, Portrait setting: 0 - 20 degrees forward

Operating Environment Temperature: 0° to 40°C (32 °F to 104 °F) / Humidity: 20-80% (Non condensation) / for up to 0-1400 m (4593 ft) altitude. Temperature 0 °C to 35 °C (32 °F to 95 °F) Altitude 1400-2800 m (4593 ft to 7874 ft)

Operating time\*2 24 h/day

Options SNMP Support: Ver. 3.0 Multi Monitoring & Control Software: Ver. 3.1 Windows only Early Warning Software: ET-SWA100 Series Whiteboard Software\*3: Downloadable for free - for Windows and Mac OS

Note \*1: When installing the display vertically, be sure that the power indicator comes to the right side. Please contact your sales representative with regard to the tilt angle before installation.\*2: In case running for a long time, the moving image is recommended to be displayed. If you display a still picture for an extended period, the image retention might remain on the screen. However, image retention can gradually disappear by displaying a moving images.\*3: Downloadable for free. For more information, please visit Global website. <https://panasonic.net/cns/prodisplays/download/software/whiteboard/>\*4 Limited performance. \*5: When the slot is not in use. \*6 Dimensions including SDM-Slot.