

---

## Inteligentna Elektronika

Ul. Raduńska 36A  
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl

---



**Panasonic**  
ideas for life

Nazwa

**Monitor Panasonic 3D Full HD Plasma  
Display TH-103VX200E**

Cena

**0,00 zł**

Producent

**Panasonic**

---

## OPIS PRODUKTU

### Product specifications

#### DISPLAY

##### Screen Size

TH-103VX200U: 102.4-inch (2,603 mm)

TH-103VX200W: 103-inch (2,603 mm)

##### Aspect Ratio

16:9

##### Effective Display Area (W x H)

2,269 x 1,276 mm (89.3" x 50.2")

##### Resolution (H x V)

1,920 x 1,080 pixels

##### Pixel Pitch (H x V)

1.182 x 1.182 mm (0.046" x 0.046")

##### Contrast Ratio

5,000,000:1\*1

##### Gradation

8,192 steps (equivalent)

##### Panel Life\*2

Approx. 100,000 hours

##### Full HD 3D

Yes

##### Connection Terminal

Component/RGB IN, Audio IN (L/R) HDMI IN x 4 PC IN, Audio IN (L/R) Audio Line OUT (L/R), OUTPUT LEVEL: VARIABLE(-∞ to 0 dB)

##### Control Terminal

Serial

D-SUB 9-pin x 1 (EXTERNAL CONTROL TERMINAL), RS-232C COMPATIBLE

LAN

RJ45 10BASE-T/100BASE-TX, COMPATIBLE with PjLINK™

3D Shutter Out

M3 Jack x 1 (for Optional 3D IR Transmitter)

Electrical

Power Requirements

200 - 240 V AC, 50/60 Hz

Power Consumption

TH-103VX200U: 1,400 W

TH-103VX200W: 1,450 W

On Average Power Consumption\*3

942 W

Power off Condition

0.3 W

Stand-by Condition

0.5 W

Mechanical

Dimensions (W x H x D)

2,412 x 1,419 x 129\*4 mm (95.0" x 55.9" x 5.1"\*4)

Weight (approx.)

Approx. 199 kg (438.7 lbs.)

Operation Environment

Temperature

0°C to 40°C (32°F to 104°F)

Humidity (Non condensation)

20% to 80%

Altitude

0 to 2,400 m (0 to 7,800 feet)

NOTE

\*1: The dark-room contrast ratio of the panel unit that can be displayed simultaneously on the same screen. Measured in "Dynamic" picture mode using a white signal in a 4% window.

\*2: Guideline operating hours before the panel brightness is reduced to half when the panel is used to display motion pictures in the Standard mode.

Afterimages (burned-in images) and malfunctions are not taken into consideration.

\*3: Based on IEC 62087 Ed.2 measurement method.

\*4: Exclusive of portion (141 mm [5.6"]) when including the protruding portion of the slot).