

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



Panasonic
ideas for life

Nazwa **Monitor Panasonic SQ1 Series TH-65SQ1**

Cena **0,00 zł**

Producent **Panasonic**

OPIS PRODUKTU

Dane techniczne:

PRODUCT SPECIFICATIONS

Screen size (diagonal) (inch)

65-inch (1638.9 mm)

Screen size (diagonal) (mm)

1638.9 mm

Aspect Ratio

16:9

Panel Type

IPS Panel / Edge-LED

Effective display area (W x H) (mm)

1428.4 x 803.5 mm

Effective display area (W x H) (inch)

56.23 x 31.63 inch

Resolution

3840 x 2160

Brightness (typ.)

500 cd/m²

Contrast Ratio

1100:1 (Typ)

Response Time

8 ms (G to G)

Terminals | HDMI IN

HDMI TYPE-A Connector x 2

Terminals | DisplayPort IN

DisplayPort x 1

Terminals | DisplayPort OUT

DisplayPort x 1

Terminals | DVI-D IN/AUDIO IN (L/R)

DVI-D 24-pin x 1/ Stereo Mini Jack (M3) x 2 (Shared with PC In)

Terminals | PC IN/AUDIO IN (L/R)

Mini D-sub 15-pin x 1/ Stereo Mini Jack (M3) x 2 (Shared with DVI-D In)

Terminals | USB

USB Connector (TYPE A) x 2, DC 5 V/2 A (USB 3.0 supported)

Terminals | Serial

D-sub 9-pin x 1, RS232C Compatible

Terminals | IR IN / OUT

Stereo Mini Jack (M3) x 1 / x 1

Built-in Speaker

TBD

Power Requirements

220-240 V AC, 50/60 Hz

Power consumption

TBD

Power Off Condition

TBD

Stand-by Condition

TBD

Dimensions (W x H x D) (mm)

1458 x 836 x 74 mm

Dimensions (W x H x D) (inch)

57.40" x 32.90" x 2.91"

Carton Size (W x H x D) (mm)

TBD

Carton Size (W x H x D) (inch)

TBD

Bezel width (mm)

11.7 mm (T), 15.3 mm (B), 12.2 mm (L/R)

Bezel width (inch)

0.46(T), 0.6"(B), 0.48" (L/R)

Operating Time

24 h/day

Weight (kg)

TBD

Weight (lbs.)

TBD

Wall-hanging pitch (inch)

15.8" x 15.8" VESA Compliant

Viewing angle [(T/B)/(L/R)]

178°/178° (CR10)

Terminals | AUDIO OUT

30 W [15 W + 15 W] 10% THD

Wall-hanging pitch (mm)

400 x 400 mm VESA Compliant

Terminal | DIGITAL LINK

RJ45 x 1, 100 BASE-TX, Compatible with long reach mode and PLink™

Terminal | LAN

RJ45 x 1, 10 BASE-T / 100 BASE-TX, Compatible with PLink™

Operating environment | Temperature

Temperature: 0 °C to 40 °C (32 °F to 104 °F)/Humidity: 20-80 % (Non condensation)/for up to 0-1400 m (4593 ft) altitude. Temperature: 0 °C to 35 °C (32 °F to 95 °F)/Altitude 1400 -2800 m (4593 ft to 7874 ft)

Orientation

TBD

Tilting angle

TBD

Terminals | Slot

Intel® SDM specification

Corresponding size SDM-S / SDM-L, Supply power 12 V / 5.5 A, 3.3 V / 1.1 A