

## Inteligentna Elektronika

Ul. Raduńska 36A  
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



**Panasonic**  
ideas for life

Nazwa **Monitor Panasonic SQ1 Series TH-75SQ1**

Cena **0,00 zł**

Producent **Panasonic**

## OPIS PRODUKTU

Screen size (diagonal) (inch) 74.5 inch

Screen size (diagonal) (mm) 1892.7 mm

Aspect Ratio 16:9

Panel Type IPS / Edge LED

Effective display area (W x H) (mm) 1649.6 mm / 927.9 mm

Effective display area (W x H) (inch) 64.94" / 36.53"

Resolution 3840 x 2160

Brightness (typ.) 500 cd/m<sup>2</sup>

Contrast Ratio 1200:1

Dynamic Contrast ratio 50000:1

Response Time 8.0 ms (G to G)

Viewing angle [(T/B)/(L/R)] 178°/ 178° (CR $\square$ 10)

Panel Surface Treatment Anti glare type (Haze 28%)

Terminals | HDMI In HDMI Type A Connector x 2(Compatible with HDCP 2.2)AUDIO: Linear PCM (Sampling frequency $\square$ 48 kHz/44.1 kHz/32 kHz)

Terminals | DVI-D IN/AUDIO IN (L/R) DVI-D 24-pin x 1 (Compatible with HDCP 1.1) Compliance with DVI Revision 1.0

Terminals | PC IN/AUDIO IN (L/R) Mini D-Sub 15-pin (DDC2B) x 1 Y/GPB/CB/BPR/CR/RHD/VD: with sync 1.0 V [p-p] (75  $\Omega$ ): without sync 0.7 V [p-p] (75  $\Omega$ ): without sync 0.7 V [p-p] (75  $\Omega$ ): without sync 0.7 V [p-p] (75  $\Omega$ ): HD/VD TTL (high impedance)

Terminals | DisplayPort IN Display Port x 1(Compatible with HDCP 2.2)AUDIO: Linear PCM (Sampling frequency $\square$ 48 kHz/44.1 kHz/32 kHz)

Terminals | DisplayPort OUT Display Port x 1 (Compatible with HDCP 1.4)

Terminals | USB USB Connector (Type A) x 2, DC 5 V/2A, DC 5 V/1A (USB 3.0 is supported)

Terminals | Serial D-sub 9-pin x 1, RS-232C Compatible

Terminal | LAN RJ45 x 1 compatible with PLinkTMRJ45 10BASE10-T/100BASE-TX

Terminal | DIGITAL LINK RJ45 x 1 100BASE-TX, compatible with Long reach mode (Compatible with

HDCP 2.2)

Terminals | Slot Intel® SDM specification Corresponding size SDM-S / SDM-L, Supply power 3.3 V / 1.1 A, 12 V / 5.5 A

Terminals | IR IN / OUT Stereo Mini Jack (M3) x 1 / x 1

Terminals | Audio Out Stereo Mini Jack (M3) x 1 □ 0.5 V [rms] Variable (- ∞ - 0 dB) (1 kHz 0 dB Input, 10 kΩ Load)

Built-in Speaker 20 W [10 W + 10 W]

Power Requirements AC 110 - 240 V 50 Hz / 60 Hz

Power Consumption 385 W

Power Off Condition approx. 0.3 W

Stand-by Condition approx. 0.5 W

Dimensions (W x H x D) (mm) 1681 x 959 x 73 mm \*Including handles

Dimensions (W x H x D) (inch) 66.15" x 37.75" x 2.87" \*Including handles

Bezel width (mm) T/B/L/R: 14.8 mm

Bezel width (inch) T/B/L/R: 0.58"

Weight (kg) approx. 56.0 kg

Weight (lbs.) 123.5 lbs

Gross Weight (kg) 71 kg

Gross Weight (lbs.) 156.6 lbs

Wall-hanging pitch (mm) VESA Compliant W 600 x H 400 mm (Installed by: M6 screws / Screw hole depth 10 mm)

Orientation Landscape/Portrait

Tilting angle Landscape : 0 - 45 degrees forward / backward Portrait : 0 - 20 degrees forward / backward

Operating Time 24h / day

Operating environment | Temperature 0 °C to 40 °C

Operating Environment | Humidity 20% to 80% (No condensation)