

## Inteligentna Elektronika

Ul. Raduńska 36A  
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



**Panasonic**  
ideas for life

Nazwa **Monitor Panasonic TH-75SQ1H**

Cena **0,00 zł**

Producent **Panasonic**

## OPIS PRODUKTU

Screen size (diagonal) (inch) 75-inch class (1892.7mm)

Panel Type IPS / D-LED

Aspect Ratio 16:9

Effective display area (W x H) (mm) 1649.6 x 927.9 mm

Effective display area (W x H) (inch) 64.94" x 36.53"

Resolution 3840 x 2160

Brightness (typ.) 1500 cd/m<sup>2</sup>

Contrast Ratio 1200:1

Response Time 10.0 ms (G to G)

Viewing angle [(T/B)/(L/R)] 178° / 178° (CR>10)

Panel Surface Treatment Anti-glare type (Haze 1 %)

Terminals | HDMI In HDMI TYPE-A Connector x 2 (Compatible with HDCP 2.2)

Terminals | DisplayPort IN DisplayPort x 1 (HDCP2.2)

Terminals | DisplayPort OUT DisplayPort x 1 (HDCP1.4)

Terminals | IR IN / OUT Stereo Mini Jack (M3) x 1 / x 1

Terminals | Audio In Stereo Mini Jack (M3) x 1 0.5V [rms] (Shared each video input except USB and MEMORY VIEWER)

Terminals | Audio Out Stereo Mini Jack (M3) x 1, 0.5 V [rms], Variable (-∞ ~ 0 dB) (1 kHz 0 dB Input, 10 kΩ Load)

Terminal | LAN RJ45 x 1, 10 BASE-T / 100 BASE-TX, Compatible with PLink™

Terminals | Slot Intel® SDM specification Corresponding size SDM-S/SDM-L, Supply power 3.3 V/MAX 1.1 A, 12 V/MAX 5.5 A

Terminals | USB USB Connector (TYPE-A) x 2, DC 5 V/2 A, DC 5V/1A (USB 3.0 Supported)

External Speaker 30 W [15 W + 15 W] (10% THD)

Built-in Speaker 20 W [10 W + 10 W]

Power Requirements 110–127 V AC, 50/60 Hz, 220–240 V AC, 50/60 Hz

Power Consumption 720 W

Power Off Condition Approx. 0.3 W

Stand-by Condition Approx. 0.5 W

Dimensions (W x H x D) (mm) 1684 x 962 x 96\* mm

Dimensions (W x H x D) (inch) 66.28" x 37.86" x 3.75"

Weight (kg) Approx. 42.2 kg (93.0 lbs)

Bezel width (mm) 14.9 mm(T/B/L/R)

Bezel width (inch) 0.6" (T/B/L/R)

Wall-hanging pitch (mm) VESA Compliant 600 x 400 mm (23.6" x 15.8") M8

Orientation Landscape/Portrait\*1

Tilting angle Landscape : 0-20 degrees forward / backward Portrait : 0-20 degrees forward / backward

Operating Environment Temperature: 0 °C to 40 °C (32 °F to 104 °F)/Humidity: 20-80 % (Non condensation)/for up to 0-1400 m (4593 ft) altitude. Temperature: 0 °C to 35 °C (32 °F to 95 °F)/Altitude 1400 -2800 m (4593 ft to 7874 ft)

Terminals | DVI-D In DVI-D 24-pin x 1 (HDCP 1.1)

Terminals | Serial In D-sub 9-pin x 1, RS232C Compatible

Terminals | DIGITAL LINK RJ45 x 1, 100 BASE-TX, Compatible with long reach mode and PLink™

Terminals | Sensor 4-pole sub-mini jack x 1

Operating time\*2 24 h/day

Note \*1: When installing the display vertically, be sure that the power indicator comes to the right side.  
\*2: In case of long time, the moving image is recommended to be displayed. If you display a still picture for an extended period, the image retention might remain on the screen. However, image retention can gradually disappear by displaying a moving images. \* The handlepart excluded, the thickness is 82mm (3.22")