

## Inteligentna Elektronika

Ul. Raduńska 36A  
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



**Panasonic**  
ideas for life

Nazwa **Monitor Panasonic TH-84LQ70L**

Cena **0,00 zł**

Producent **Panasonic**

## OPIS PRODUKTU

### Model

TH-98LQ70

TH-84LQ70

TH-98LQ70L

TH-84LQ70L

### Display

Screen Size (Diagonal)

98-inch

84-inch

98-inch

84-inch

### Panel Type

IPS / Direct-LED

IPS / Edge-LED

IPS / Direct-LED

IPS / Edge-LED

### Aspect Ratio

16:9

### Effective Display Area (W x H)

2159 x 1215 mm (85.0" x 47.8")

1861 x 1047 mm (73.3" x 41.3")

2159 x 1215 mm (85.0" x 47.8")

1861 x 1047 mm (73.3" x 41.3")

### Number of Pixels (H x V)

3840 x 2160 pixels

### Brightness (Typ)

500 cd/m<sup>2</sup>

## Dynamic Contrast Ratio

500000 : 1

## Contrast Ratio

1300 : 1

1400 : 1

1300 : 1

1400 : 1

## Response Time

8 ms

12 ms

8 ms

12 ms

## Viewing Angle (Horizontal/Vertical)

178° / 178°

178° / 178°

178° / 178°

178° / 178°

## Connection Terminal

### HDMI In

HDMI TYPE A Connector x 2 (Up to 4K@ 50/60 Hz)\*1,

HDMI TYPE A Connector x 2 (Up to 2K@ 50/60 Hz)\*1

### DisplayPort In

DisplayPort x 1 (DP1.2a) \*1

### DVI-D In/Audio In (L/R)

DVI-D 24-pin x 1/Stereo Mini Jack (M3) x 1 set (Shared with PC In)

### PC In/Audio In (L/R)

Mini D-sub 15-pin x 1(Female) \*2/Stereo Mini Jack (M3) x 1 set (Shared with DVI-D In)

### Function Slot

SLOT NX x 2 (Vacant)

## Control

### Serial In / Out

D-sub 9-pin x 1, RS-232C Compatible

### LAN

RJ45 x 1 100BASE-TX, Compatible with PLink™ (Shared with DIGITAL LINK)

### DIGITAL LINK

RJ45 x 1 ( Shared with LAN )

## Audio

### Audio Out

Stereo Mini Jack (M3) x 1

### Built in Speaker

20 W [10 W + 10 W] (10 % THD)

## Electrical

### Power Requirements

110-127 V (U model)/220-240 V (W model), AC, 50/60 Hz

### Power Consumption

650 W (U model), 620 W (W model)

560 W (U model), 540 W (W model)

650 W (U model), 620 W (W model)

560 W (U model), 540 W (W model)

## Mechanical

### Dimensions (W×H×D)

2233 x 1288 x 122 mm

(87.9" x 50.7" x 4.8" )

1949 x 1141 x 99 mm

(76.7" x 44.9" x 3.9" )

2233 x 1288 x 113 mm (87.9" x 50.7" x 4.4")

1949 x 1141 x 92 mm (76.7" x 44.9" x 3.6")

Weight

Approx. 136.0 kg (299.9 lbs.)

Approx. 108.0 kg (238.1 lbs.)

Approx. 105 kg (231.5 lbs.)

Approx. 84 kg (185.2 lbs.)

Protective Glass

YES

YES

NO

NO

Installation Requirement

Orientation

Landscape/Portrait

Tilting Angle

10 degrees with landscape setting and 5 degrees with portrait setting\*

Operating Environment

Temperature: 0°C to 40°C (32°F to 104°F)/Humidity: 20 % to 80 % (Non condensation)/ Altitude 0~2400 m (7874 ft)\*3

Operating Time\*4

24 h/day