

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl

Panasonic
ideas for life



Nazwa **Monitor Panasonic TH-86SQ1H**

Cena **0,00 zł**

Producent **Panasonic**

OPIS PRODUKTU

Screen size (diagonal) (inch) 86-inch class (2174.2 mm)

Panel Type IPS / D-LED

Aspect Ratio 16:9

Effective display area (W x H) (mm) 1895.0 x 1065.9 mm

Effective display area (W x H) (inch) 74.60" x 41.96"

Resolution 3840 x 2160

Brightness (typ.) 1200 cd/m²

Contrast Ratio 1200:1

Response Time 8.0ms (G to G)

Viewing angle [(T/B)/(L/R)] 178° / 178° (CR>10)

Panel Surface Treatment Anti-glare low reflection type (Haze 3 %)

Terminals | HDMI In HDMI TYPE-A Connector x 2 (Compatible with HDCP 2.2)

Terminals | DisplayPort IN DisplayPort x 1 (HDCP2.2)

Terminals | DisplayPort OUT DisplayPort x 1 (HDCP1.4)

Terminals | IR IN / OUT Stereo Mini Jack (M3) x 1 / x 1

Terminals | Audio In Stereo Mini Jack (M3) x 1 0.5V [rms] (Shared each video input except USB and MEMORY VIEWER)

Terminals | Audio Out Stereo Mini Jack (M3) x 1, 0.5 V [rms], Variable (-∞ ~ 0 dB) (1 kHz 0 dB Input, 10 kΩ Load)

Terminal | LAN RJ45 x 1, 10 BASE-T / 100 BASE-TX, Compatible with PLink™

Terminals | Slot Intel® SDM specification Corresponding size SDM-S/SDM-L, Supply power 3.3 V/MAX 1.1 A, 12 V/MAX 5.5 A

Terminals | USB USB Connector (TYPE-A) x 2, DC 5 V/2 A, DC 5V/1A (USB 3.0 Supported)

Built-in Speaker 20 W [10 W + 10 W]

Power Requirements 110–127 V AC, 50/60 Hz, 220–240 V AC, 50/60 Hz

Power Consumption 730 W

Power Off Condition Approx. 0.3 W

Stand-by Condition Approx. 0.5 W

Dimensions (W x H x D) (mm) 1929 x 1100 x 96* mm

Dimensions (W x H x D) (inch) 75.95" x 43.31" x 3.75"

Weight (kg) Approx. 57.8 kg (127.4 lbs)

Bezel width (mm) 15.5 mm (T/B/L/R)

Bezel width (inch) 0.7" (T/B/L/R)

Wall-hanging pitch (mm) VESA Compliant 600 x 400 mm (23.6" x 15.8") M8

Orientation Landscape/Portrait*1

Tilting angle Landscape : 0-20 degrees forwardPortrait : 0-20 degrees forward

Operating Environment Temperature: 0 °C to 40 °C (32 °F to 104 °F)/Humidity: 20-80 % (Non condensation)/for up to 0-1400 m (4593 ft) altitude. Temperature: 0 °C to 35 °C (32 °F to 95 °F)/Altitude 1400 -2800 m (4593 ft to 7874 ft)

External Speaker 30 W [15 W + 15 W] (10% THD)

Note *1: When installing the display vertically, be sure that the power indicator comes to the right side.

*2: In case of long time, the moving image is recommended to be displayed. If you display a still picture for an extended period, the image retention might remain on the screen. However, image retention can gradually disappear by displaying a moving images. * The handlepart excluded, the thickness is 82mm (3.22")

Terminals | DVI-D In DVI-D 24-pin x 1 (HDCP 1.1)

Terminals | Serial In D-sub 9-pin x 1, RS232C Compatible

Operating time*2 24 h/day

Terminals | Sensor 4-pole sub-mini jack x 1

Terminals | DIGITAL LINK RJ45 x 1, 100 BASE-TX, Compatible with long reach mode and PLink™