

## Inteligentna Elektronika

Ul. Raduńska 36A  
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



**Panasonic**  
ideas for life

Nazwa **Monitor Panasonic TH-98SQE1**

Cena **0,00 zł**

Producent **Panasonic**

## OPIS PRODUKTU

Screen size (diagonal) (inch) 98-inch class (2476.9 mm)

Aspect Ratio 16:9

Panel Type IPS/D-LED

Effective display area (W x H) (mm) 2158.8 x 1214.3 mm

Effective display area (W x H) (inch) 84.99" x 47.80"

Resolution 3840 x 2160

Brightness (typ.) 500 cd/m<sup>2</sup>

Contrast Ratio 1200:1

Response Time 8.0 ms (G to G)

Viewing angle [(T/B)/(L/R)] 178° / 178° (CR>10)

Power Requirements 110–127 V AC, 50/60 Hz, 220–240 V AC, 50/60 Hz

Terminals | HDMI In HDMI TYPE-A Connector x 4 (HDCP 2.2 supported)

Terminals | DisplayPort IN DisplayPort x 1

Terminals | DisplayPort OUT DisplayPort x 1

Terminals | USB USB Connector (TYPE-A) x 2, (Type-C) x 1, Internal (Type-A) x 1

Terminals | Serial D-sub 9-pin x 1, RS232C Compatible

Terminal | LAN RJ45 x 1

Terminals | Slot x1 (Intel® SDM Specification Capability)

Terminals | Audio Out Stereo Mini Jack(M3) x1, SPDIF x 1

Built-in Speaker 24 W [12 W + 12 W]

Power Consumption 703 W

Power Off Condition 0 W

Stand-by Condition Approx. 0.5 W

Dimensions (W x H x D) (mm) 2216 x 1271 x 99 mm \*Excluding remote IR sensor

Dimensions (W x H x D) (inch) 87.25" x 50.67" x 3.88" \*Excluding remote IR sensor

Bezel width (mm) 28.2 mm (T/R/L/B)

Bezel width (inch) 1.11" (T/R/L/B)

Weight (kg) Approx.99.8 kg

Weight (lbs.) 220.1 lbs

Wall-hanging pitch (mm) VESA Compliant 800 x 400 mm

Wall-hanging pitch (inch) VESA Compliant 31.5" x 23.7"

Panel Surface Treatment Anti-glare type (Haze 25 %)

Wi-Fi Dongle, IEEE 802.11. a/b/g/n/ Dual Wi-Fi CERTIFIED

Terminals | Audio In Pin Jack x 2 (L/R)

Operating Environment Temperature: 0 °C to 40 °C (32 °F to 104 °F)/Humidity: 20-80 % (Non condensation)/for up to 0-1400 m (4593 ft) altitude. Temperature: 0 °C to 35 °C (32 °F to 95 °F)/Altitude 1400 -2800 m (4593 ft to 7874 ft)

Terminals | PC In Mini D-sub 15-pin x 1 (Female)

Terminals | IR In Stereo Mini Jack (M3) x 1

Note \*1: When installing the display vertically, be sure that the power indicator comes to the right side.

\*2: Please contact your sales representative with regard to the tilt angle before installation. \*3: In case of long time, the moving image is recommended to be displayed. If you display a still picture for an extended period, the image retention might remain on the screen. However, image retention can gradually disappear by displaying a moving images.

Orientation\*1 Landscape/Portrait

Tilting angle\*2 0-20 degrees forward with landscape/portrait setting (TBD)

Operating time\*3 24 h/day