

---

## Inteligentna Elektronika

Ul. Raduńska 36A  
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl

---



**Panasonic**  
ideas for life

Nazwa **Monitor Panasonic TH50PF30U**

Cena **0,00 zł**

Producent **Panasonic**

---

## OPIS PRODUKTU

Screen Size (Diagonal)

50"

Aspect Ratio

16:9

Pixel Resolution

1920 x 1080 pixels (1 pixel = 3 cells for R, G and B)

Number of Pixels

2,073,600 (1920 x 1080)

Display Area

43.5 x 24.4" (1105 x 622mm)

Gradation

6144 equivalent

Panel Life

Approx. 100,000 hours

Contrast Ratio

5,000,000:1

3D

Yes (full HD 3D ready)

Video System

ATSC/PAL/NTSC

HDTV Compatibility

Yes

TV Scan Lines

Up to 1080

CableCARD Slot

No

#### Inputs/Outputs

Video in: BNC x 1 1.0v [p-p] (75 Ω)

Audio in (L/R): RCA pin jack x 1 1.0v [p-p] (75 Ω)

Component/RGB in: BNC X 3 Y/G: with sync 1.0V [p-p] (75Ω), B/PB,/CB, R/PR/CR: 0.7 V [p-p] (75Ω)

HDMI in: HDMI type A connector x 1

DVI-D in: DVI-D 24 pin x 1, compliance with DVI revision 1.0, compatible with HDCP 1.1

Audio in: M3 jack x 1 0.5V [rms]

PC in: HD/VD: 1.0-5.0V [p-p] (high impedance), HD/VD: 1.0~5.0V [p-p] (high impedance)

Function slot: SLOT 2.0: 1 (vacant)

LAN: RJ-45 10 Base-T/100 BASE -TX, compatible with PJ link

Serial: D-sub 9-pin x 1 (external control terminal), RS-232C compatible

3D shutter out: M3 jack x 1 (for 3D IR transmitter)

DC 8V out for 3D IR transmitter: center plus for EIAJ 4mm plug

#### Color

Black

#### Audio Output

6Ω, 16W [8W + 8W] (10% THD)

#### Remote Control

Power requirements: DC 3 V (2 x AA batteries)

Operation distance: 23' (7 m) in front of plasma display

Weight: 3.5 oz (100 g) including batteries

#### Power Requirements

110-127V AC, 50Hz/60Hz

#### Power Consumption

Power consumption: 475W

On mode average power consumption: 220W

Power off condition: 0.2W

Standby condition: Save on 0.4W, Save off 0.7W

#### Environmental Conditions

Operating temperature: 32-104°F (0-40°C)

Storage temperature: -4-140°F (-20-60°C)

Operating humidity: 20-80% (non condensation)

Storage humidity: 20-90% (non condensation)

Operating altitude: 0-9100' (0-2800 m)

Storage altitude: 0-10,800' (0-3300 m)

ENERGY STAR Qualified

Yes

#### Regulations

Safety regulations: UL60065 CAN/CSA-22.2 No. 60065:03, NOM approval

Radiation regulation: FCC Part 15 Class-B, ICES-003

#### Dimensions (WxHxD)

47.7 x 28.5 x 3.5" (1210 x 724 x 89mm)

#### Weight

72.8 lb. (33kg)