
Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl

Panasonic
ideas for life



Nazwa **Monitor Sietciowy Panasonic TH-50LFC70E**

Cena **10 061,00 zł**

Producent **Panasonic**

OPIS PRODUKTU

Model

TH-80LFC70

TH-65LFC70

TH-50LFC70

Display

Screen Size (Diagonal) / Aspect Ratio

80-inch (2,032 mm) / 16:9

65-inch (1,638 mm) / 16:9

50-inch (1,257 mm) / 16:9

Panel Type

LCD VA Panel/E-LED

Effective Display Area

(W x H)

1,771 x 996 mm

(69.7" x 39.2")

1,428 x 803 mm

(56.2" x 31.6")

1,095 x 616 mm

(43.1" x 24.3")

Number of Pixels (H x V)

1,920 x 1,080 pixels

Brightness

350 cd/m² (Typ)

350 cd/m² (Typ)

350 cd/m² (Typ)

Contrast Ratio

5,000:1

4,000:1

5,000:1

Response Time

4 ms (G to G)

6.5 ms (G to G)

6.5 ms (G to G)

Viewing Angle

176°/176°

178°/178°

176°/176°

Connection Terminal

VIDEO In

BNC x 1

Audio In (L/R)

Stereo Mini Jack (M3) x 1 (Shared with Component/RGB In)

HDMI In

HDMI Type A Connector x 2

Component/RGB In

BNC x 1 set

Audio In (L/R)

Stereo Mini Jack (M3) x 1 (Shared with VIDEO In)

DVI-D In

DVI-D 24-pin x 1

Audio In (L/R)

Stereo Mini Jack (M3) x 1 (Shared with PC In)

PC In

Mini D-Sub 15-pin x1 (Female), Plug & Play (VESA DDC 2B)

Audio In (L/R)

Stereo Mini Jack (M3) x 1 (Shared with DVI-D In)

PC Out

Mini D-sub 15-pin x 1

USB A

USB TYPE A Connector x 1 (For Memory Viewer)

Control Terminal

Serial

D-Sub 9-pin x 1, RS-232C Compatible

DIGITAL LINK

RJ45 x 1 (Shared with LAN)

LAN

RJ45 x 1, 100BASE-TX, Compatible with PLink™ (Shared with DIGITAL LINK)

Function Slot

SLOT2.0 x 1

Audio

Built-in Speaker

20 W [10 W + 10 W]

External Speaker

8 Ω, 20 W [10 W + 10 W] (10 % THD)

8 Ω, 20 W [10 W + 10 W] (10 % THD)

8 Ω, 20 W [10 W + 10 W] (10 % THD)

Electrical

Power Requirements

110-127 V/220-240 V AC, 50/60 Hz

Power Consumption

345 W

210 W

135 W

Power Off Consumption

Approx. 0.3 W

Stand-by Condition

Approx. 0.5 W

Mechanical

Dimensions

(W x H x D)

1,868 x 1,093 x 99 mm

(73.6" x 43.1" x 3.9")

1,484 x 859 x 97 mm

(58.5" x 33.8" x 3.9")

1,151 x 672 x 94 mm

(45.4" x 26.5" x 3.7")

Bezel Width

Approx. 45 mm (1.8")

Approx. 25 mm (1.0")

Approx. 25 mm (1.0")

Weight

Approx. 83.0 kg

(183.0 lbs.)

Approx. 55.0 kg

(121.3 lbs.)

Approx. 30.0 kg

(66.1 lbs.)

Pitch for Wall-Hanging

VESA Compliant 400 x 400 mm (15.8" x 15.8")

684 x 300 mm (27.0" x 11.9")

400 x 300 mm (15.8" x 11.9")

Protective Glass Thickness

Approx. 4 mm (0.2") /Anti-Glare

Approx. 3.2 mm (0.13") /Anti-Glare

Approx. 2.5 mm (0.1") /Anti-Glare

Operating Environment

Temperature: 0 °C to 40 °C / Humidity: 20 % to 80 % (Non Condensation)