

---

## Inteligentna Elektronika

Ul. Raduńska 36A  
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl

---

**Panasonic**  
ideas for life



Nazwa **Monitor Sieczowy Panasonic TH-80LFC70E**

Cena **43 271,00 zł**

Producent **Panasonic**

---

## OPIS PRODUKTU

Model

TH-80LFC70

Display

Screen Size (Diagonal) / Aspect Ratio

80-inch (2,032 mm) / 16:9

Panel Type

LCD VA Panel/E-LED

Effective Display Area

(W x H)

1,771 x 996 mm

(69.7" x 39.2")

Number of Pixels (H x V)

1,920 x 1,080 pixels

Brightness

350 cd/m<sup>2</sup> (Typ)

Contrast Ratio

5,000:1

Response Time

4 ms (G to G)

Viewing Angle

176°/176°

Connection Terminal

VIDEO In  
BNC x 1  
Audio In (L/R)  
Stereo Mini Jack (M3) x 1 (Shared with Component/RGB In)  
HDMI In  
HDMI Type A Connector x 2  
Component/RGB In  
BNC x 1 set  
Audio In (L/R)  
Stereo Mini Jack (M3) x 1 (Shared with VIDEO In)  
DVI-D In  
DVI-D 24-pin x 1  
Audio In (L/R)  
Stereo Mini Jack (M3) x 1 (Shared with PC In)  
PC In  
Mini D-Sub 15-pin x1 (Female), Plug & Play (VESA DDC 2B)  
Audio In (L/R)  
Stereo Mini Jack (M3) x 1 (Shared with DVI-D In)  
PC Out  
Mini D-sub 15-pin x 1  
USB A  
USB TYPE A Connector x 1 (For Memory Viewer)  
Control Terminal  
Serial  
D-Sub 9-pin x 1, RS-232C Compatible  
DIGITAL LINK  
RJ45 x 1 (Shared with LAN)  
LAN  
RJ45 x 1, 100BASE-TX, Compatible with PLink™ (Shared with DIGITAL LINK)  
Function Slot  
SLOT2.0 x 1  
Audio  
Built-in Speaker  
20 W [ 10 W + 10 W]  
External Speaker  
8 Ω, 20 W [ 10 W + 10 W] (10 % THD)  
Electrical  
Power Requirements  
110-127 V/220-240 V AC, 50/60 Hz  
Power Consumption  
345 W  
Power Off Consumption  
Approx. 0.3 W  
Stand-by Condition  
Approx. 0.5 W  
Mechanical  
Dimensions  
(W x H x D)  
1,868 x 1,093 x 99 mm  
(73.6" x 43.1" x 3.9")  
Bezel Width  
Approx. 45 mm (1.8")  
Weight  
Approx. 83.0 kg  
(183.0 lbs.)

Pitch for Wall-Hanging

VESA Compliant 400 x 400 mm (15.8" x 15.8")

Protective Glass Thickness

Approx. 4 mm (0.2") /Anti-Glare

Operating Environment

Temperature: 0 °C to 40 °C / Humidity: 20 % to 80 % (Non Condensation)