

Inteligentna Elektronika

Ul. Raduńska 36A
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl



Panasonic
ideas for life

Nazwa **Projektor Panasonic PT-RZ575**

Cena **0,00 zł**

Producent **Panasonic**

OPIS PRODUKTU

Specifications (Tentative)

*1 When Standby Mode is set to Eco, network functions such as power on over LAN will not operate. Measurement, measuring conditions, and method of notation all comply with ISO 21118 international standards.

*2 With operation mode set to Normal.

*3 Only compatible with dot clock frequency of 27 MHz (pixel repetition signal).

*4 WUXGA resolution supports CVTRB signals (WUXGA60RB) and CVT (WUXGA60/WUXGA50) signals.

When installed in conventional orientation, upper side and right side facing toward the screen are .

When installed on the ceiling, bottom side and left side are .

*5 Average value. May differ depending on the actual unit.

*6 With legs at shortest position.

*7 The operating environment temperature should be between 0 °C (32 °F) and 40 °C (104 °F) when the projector is used at altitudes between 1,400 m (4,593 ft) and 4,200 m (13,780 ft) above sea level. When PROJECTOR SETUP menu OPERATION SETTING OPERATING MODE is set to ECO or SILENT, the projector cannot be used at an altitude of 2,700 m (8,858 ft) or higher above sea level. When using the projector at an altitude lower than 2,700 m (8,858 ft) above sea level and the operating environment temperature is 35 °C (95 °F) or higher, light output may be reduced to protect the projector. When using the projector at an altitude between 2,700 m (8,858 ft) and 4,200 m (13,780 ft) and the operating environment temperature is 25 °C (77 °F) or higher, light output may be reduced to protect the projector.