

## Inteligentna Elektronika

Ul. Raduńska 36A  
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl

**Panasonic**  
ideas for life



Nazwa **Projektor Panasonic PT-VW360EJ**

Cena **3 699,00 zł**

Producent **Panasonic**

## OPIS PRODUKTU

LCD panel

Rozmiar

15.0 mm (0.59 in) (16:10 aspect ratio)

Display method □ Transparent LCD panel (× 3, R/G/B)

Pixels □ 1,024,000 (1280 x 800) pixels

Obiektyw □ Manual zoom (1.6x)

Manual focus,

F 1.60–1.90, f 15.31–24.64 mm

Screen size □ 0.76–7.62 m (30–300 in), 16:10 aspect ratio

Jasność\*1 □ 4,000 lm (input signal: PC, lamp power: NORMAL,

picture mode: Dynamic, Iris: Off,

Daylight View: Off, Auto Power Save: Off)

Rozdzielczość □ 1280 x 800 pixels

(Input signals that exceed this resolution will be converted to 1280 x 800 pixels)

Lamp □ 240 W x 1 lamp

Czas wymiany lampy □ NORMAL: 5,000 hours / ECO: 7,000 hours

Center-to-corner uniformity\*1 □ 85%

Contrast\*1 □ 20,000:1 (Full On/Off) (input signal: PC, lamp power: NORMAL, picture mode: Dynamic, Iris:

On, Daylight View: Off, Auto Power Save: Off)

Optical axis shift □ 49:1 (fixed)

Keystone correction range □ Vertical: ±35° (±30° when using AUTO) Horizontal: ±35°

Installation □ Ceiling/floor, front/rear

Optical axis shift (from center of screen)

Power supply □ AC 100–240 V, 50 Hz/60 Hz

Power consumption □ 320 W (0.5 W when Standby mode set to ECO\*2,

1.0 W when Standby mode set to Network,

8.0 W when Standby mode set to NORMAL)

Built-in speaker □ 4.0 cm (1 9/16") round shape x 1, output power: 10 W (monaural)

Poziom hałas\*1 □ 37 dB (lamp power: Normal), 29 dB (lamp power: ECO)

Cabinet materials □ Molded plastic

Wymiary □ 352 x 98\*3 x 279\*4 mm (13 27/32" x 3 27/32"\*3 x 10 31/32"\*4)

Waga\*5

Approx. 3.3 kg (7.28 lbs)

Środowisko działania □ Operating temperature: 0–40 °C [32–104 °F] (less than 1,400 m [4,593 ft] above sea level, High Altitude Mode: OFF); 0–30 °C [32–86 °F] (1,400 m [4,593 ft] to 2,000 m [6,562 ft], High Altitude Mode: 1); 0–30 °C [32–86 °F] (2,000 m [6,562 ft] to 2,700 m [8,858 ft], High Altitude Mode: 2)

Operating humidity: 20–80 % (no condensation)

Applicable software □ Multi Monitoring & Control Software, Logo Transfer Software, Presenter Light for Windows®,

Wireless Projector Apps for iOS / Android™

Interfejs

HDMI 1/2 IN □ HDMI 19-pin x 2 (compatible with HDCP, Deep Color), audio signal: linear PCM (sampling frequencies: 48 kHz, 44.1 kHz, 32 kHz)

COMPUTER 1 IN □ D-sub HD 15-pin (female) x 1 (RGB, YPBPR, YCBCR, Y/C)

COMPUTER 2 IN/1 OUT □ D-sub HD 15-pin (female) x 1 (RGB, YPBPR, YCBCR), (input/output selectable using on-screen menu)

VIDEO IN □ Pin jack x 1 (Composite VIDEO)

AUDIO IN 1 □ M3 Stereo Mini Jack x 1 (L-R x 1)

AUDIO IN 2 □ M3 Stereo Mini Jack x 1 (L-R x 1)

AUDIO IN 3 □ Pin jack x 2 (L, R x 1)

VARIABLE AUDIO OUT □ M3 Stereo Mini Jack x 1 (L-R x 1) for output

LAN □ RJ-45 x 1 (for network connection, compatible with PLink™ [Class 1], 10BASE-T/100BASE-TX)

SERIAL IN □ D-sub 9-pin (female) x 1 for external control (RS-232C compliant)

USB A □ USB-Type A (for Memory Viewer / Wireless Module [Optional: ET-WML100]) x 1

USB B □ USB-Type B (for USB Display) x 1

\*1 Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2012 international standards. Value is average of all products when shipped.

\*2 When the Standby mode is set to ECO, network functions such as power on over the LAN network will not operate. Also, only certain commands can be received for external control using the serial terminal.

\*3 With legs retracted to minimum.

\*4 Including protruding parts.

\*5 Average value. May differ depending on the actual unit.