

---

## Inteligentna Elektronika

Ul. Raduńska 36A  
83-333 Chmielno

Tel.: +48 730 90 60 90

E-mail: info@centrumprojekcji.pl

---



**SAMSUNG**

Nazwa **Monitor Samsung SMART Signage ME75C (LH75MECPLGC/EN)**

Cena **0,00 zł**

Producent **Samsung**

---

## OPIS PRODUKTU

### TECH SPECS

Panel

Diagonal Size

75"

Type

240Hz LED BLU

Resolution

1,920 x 1,080 (16:9)

Pixel Pitch (mm)

0.2865(H) x 0.8595(V)

Active Display Area

1,650.24(H) x 928.26(V)

Brightness

550cd/m<sup>2</sup>

Contrast Ratio (Dynamic)

5,000:1

Viewing Angle (Horizontal/Vertical)

178° / 178°

Response Time (G-to-G)

8ms

Display Colour

10bit Dithering - 1.07Billion

Color Gamut

72%

Contrast Ratio

10,000:1 (AV Mode)

Display

H-Scanning Frequency

30 ~ 81kHz

Maximum Pixel Frequency

148.5MHz

V-Scanning Frequency

56 ~ 85kHz

Connectivity

Input

RGB

Analog D-SUB, DVI-D, Display Port 1.2

Video

HDMI1, HDMI2, Component (CVBS Common)

Audio

Stereo mini Jack

Output

RGB

DP1.2 (Loop-out)

Audio

Stereo mini Jack

External Control

RS232C (in / out) thru stereo jack, RJ45

External Sensor

IR, Ambient Light

Mechanical Specification

Dimension

Set Dimension (WxHxD)

1,678.2 x 958.7 x 48.6mm

Package Dimension (WxHxD)

1,863 x 1173 x 473mm

Weight

Set Weight

45.5kg

Package Weight

65.6kg

VESA Mount

400 x 400mm

Stand Type

Foot Stand (Optional)

Media Player Option Type

Embedded, SBB-A( Attached)

Operation

Operating Temperature

0°C ~ 40°C

Humidity

10 ~ 80%

General Feature

Key

Slim & Light LFD with Built-in MagicInfo Lite

Special

Magic Clone (to USB), Auto Source Switching & Recovery, Lamp Error Detection, Super Clear Coating, Temperature Sensor, RS232C / RJ45 MDC, Plug and Play (DDC2B), PIP / PBP, Video Wall (10 x 10), Pivot Display, Image Rotation, Button Lock, DP 1.2 Digital Daisy Chain(Supporting 2 x 2 UHD Resolution, HDCP Support), Smart Scheduling, Smart F / W update, Clock Battery(80hrs Clock Keeping)Built In MagicInfo(Lite, Premium-S, Videowall-S)

Internal Player

Processor

Cortex-A9 1GHz Dual Core CPU

On-Chip Cache Memory

L1 (I / D): 32KB / 32KB L2 (Unified): 512KB

Clock Speed

1GHz CPU Dual

Main Memory Interface

1GB Dual 32bit DDR3-667 (1,333MHz)

Graphics

2D & 3D Graphics Engine - Up to 1920 x 1080. 32bpp - Supports OpenGL ES

Storage (FDM)

4GB (1.2GB Occupied by O/S, 2.8GB Available, )

Multimedia

Video Decoder - MPEG-1/2, H.264 / AVC (Dual) - VC-1, JPEG, PNG Audio DSP (Decoder) - AC3 (DD),

MPEG, DTS and etc.

IO Ports

USB 2.0

Operating System

Linux

Power

Power Supply

AC 100 - 240V ~ (+ / - 10%), 50/60Hz

Power Consumption

Off Mode

Less than 0.5W

On Mode

319 (Max) / 290 (Typical) / 1,087.79 (BTU)

Sleep Mode

Less than 0.5W

Type

Internal

Embedded PC

CPU

SBB-A (Optional)

N/B

SBB-A (Optional)

S/B

SBB-A (Optional)

GPU

SBB-A (Optional)

FDM/HDD

SBB-A (Optional)

Memory

SBB-A (Optional)

Ethernet

SBB-A (Optional)

Connectivity

USB

SBB-A (Optional)

Output

SBB-A (Optional)

Others

SBB-A (Optional)

Certification

EMC

FCC (USA) FCC Part 15, Subpart B class A CE (Europe) EN55022, EN55024 VCCI (Japan) V-3 (CISPR22) KCC (Korea) :KN22, KN24BSMI (Taiwan) : CNS13438 (CISPR22) C-Tick (Australia) : AS/NZS3548 (CISPR22)CCC(China) :GB 9254-2008, GB 17625.1-2003

## Safety

CUL (USA + Canada) : UL60950 TUV (Germany) : EN60950 CB (Europe) : IEC60950/EN60950 EK (Korea) : K60950 CCC (China) : GB4943.1 PSB (Singapore) : IEC60950 GOST (Russia) : IEC60950, EN55022 SIQ (Slovenia) : IEC60950, EN55022 PCBC (Poland) : IEC60950, EN55022 NOM (Mexico) : NOM-001-SCFI-1993 IRAM (Argentina) : IRAM SASO (Saudi Arabia) : IEC60950 BIS(India) : IS13252

## Accessory

### Included

Quick Setup Guide, Warranty Card, Application CD, D-Sub cable, Power Cord, Remote Controller, Batteries

### Optional

#### Mount

WMN4675MD

#### Stand

STN-L75D